



PRODUCT-DETAILS

CA47B

CA47B ComfortLine Compact distribution board, Surface mounting, 336 SU, Isolated (Class II), IP30, Rows: 7, 1100 mm x 1050 mm x 160 mm



Informations générales	
Extension du type de produit	CA47B
Code de produit	2CPX052568R9999
EAN	4011617525684
Description courte	CA47B ComfortLine Compact distribution board, Surface mounting, 336 SU, Isolated (Class II), IP30, Rows: 7, 1100 mm x 1050 mm x 160 mm
Description longue	Compact distribution board, empty cabinet, for the internal use, without door, class of protection II (double insulated), in combination with earthing set (accessory) we can achieve protection class 1, degree of protection IP30, applicable standards: EN 61439-1, EN 61439-3, Rated operational voltage 400V AC 50/60 Hz, rated current 125 A, Powder-coated, in RAL 9016, enclosure out of sheet steel, without door, cable entry on top via membrane flange mounted, on bottom via flange opening pre-punched, dimensions in mm (H x W x D): 1100 x 1050 x 160, Grid unit 7 GU, panel width 4, Space units 336, without N/PE without terminal, cable fastening rail integrated, pre-assembled for installation of modules and CombiLine Modules

Technique	
Normes et standards	DIN EN 61439-3
Tension	Maximum 400 V
Courant nominal (I _n)	125 A

Power Loss	Δt = 20K 112.1 W Δt = 25K 147.9 W Δt = 30K 185.6 W
Number of Rows	7
Configuration Type	pre-assembled for installation of modules and CombiLine Modules
Cover Plate Type	optional
Type de boîtier	Compact distribution board
Type de montage	Surface mounting
Door Type	Without Door
Finition de surface	Powder-coated
Qualité du matériau	Steel
Matériau	"
Style de cache	Closed
DIN Place Units	336
RAL Number	RAL 9016 - Blanc signalisation
Couleur	Traffic white
Type de borne	No Terminals

Material Compliance

Informations RoHS	2CPC100012X0201
Statut RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Date RoHS	20230918
REACH Declaration	2CPC100005X0201
REACH Information	False - does not contain substances > 0.1 mass percentage
REACH Date	20221108
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Environnement

Indice de protection	IP30
Classe de protection	Isolated (Class II)

Dimensions

Width in Number of Modular Spacings	48
Produit Largeur Net	1050 mm
Produit Hauteur Net	1100 mm
Produit Longueur Net	160 mm
Section Width	4
Poids net	15.181 kg
Profondeur d'encastrement (t ₂)	0 mm
Schéma dimensionnel	2CPC000012D0201

Commande

Emballage Niveau 1 Unités	pack 1 pièce
Emballage Niveau 1 Poids	17.228 kg

Certificats et Déclarations (Numéro de document)

Déclaration de Conformité - CE	2CPC100012X0201
-----------------------------------	-----------------

Installation

Instructions et manuels	No document needed
-------------------------	--------------------

Downloads Préférés

Fiche produit,	2CPC000001C0101
informations techniques	2CPC000002C0101

Classifications

ETIM 8	EC000214 - Small distribution board
ETIM 9	EC000214 - Small distribution board
Catégorie DEEE	Product Not in WEEE Scope
WEEE B2C / B2B	Business To Consumer
CN8	85381000
Code de classification d'objet	U

Catégories

Produits basse tension → Tableaux, Coffrets et Armoires → Tableaux Divisionnaires → Compact Distribution Boards - Modules Assembled → ComfortLine Compact CA

