



PRODUCT-DETAILS

CA47B

CA47B ComfortLine Compact distribution board, Surface mounting, 336 SU, Isolated (Class II), IP30, Rows: 7, 1100 mm x 1050 mm x 160 mm



Informazioni generali	
Tipo	CA47B
ID prodotto	2CPX052568R9999
EAN	4011617525684
Descrizione catalogo	CA47B ComfortLine Compact distribution board, Surface mounting, 336 SU, Isolated (Class II), IP30, Rows: 7, 1100 mm x 1050 mm x 160 mm
Descrizione	Compact distribution board, empty cabinet, for the internal use, without door, class of protection II (double insulated), in combination with earthing set (accessory) we can achieve protection class 1, degree of protection IP30, applicable standards: EN 61439-1, EN 61439-3, Rated operational voltage 400V AC 50/60 Hz, rated current 125 A, Powder-coated, in RAL 9016, enclosure out of sheet steel, without door, cable entry on top via membrane flange mounted, on bottom via flange opening pre-punched, dimensions in mm (H x W x D): 1100 x 1050 x 160, Grid unit 7 GU, panel width 4, Space units 336, without N/PE without terminal, cable fastening rail integrated, pre-assembled for installation of modules and CombiLine Modules

Dati tecnici	
Norme di riferimento	DIN EN 61439-3
Tensione nominale di funzionamento	Maximum 400 V

Corrente nominale (I _n)	125 A
Perdita di potenza	Δt = 20K 112.1 W Δt = 25K 147.9 W Δt = 30K 185.6 W
Numero di file	7
Tipo configurazione	pre-assembled for installation of modules and CombiLine Modules
Tipo di piastra di copertura	optional
Tipo contenitore	Compact distribution board
Tipo di montaggio	Surface mounting
Tipo porta	Without Door
Finitura superficie	Powder-coated
Materiale involucro	Steel
Materiale	"
Stile copertura	Closed
Numero moduli DIN	336
RAL Number	RAL 9016 - Bianco traffico
Colore	Traffic white
Tipo di morsetto	No Terminals

Material Compliance

Informazioni RoHS	2CPC100012X0201
Dichiarazione RoHS	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Data RoHS	20230918
REACH Declaration	2CPC100005X0201
REACH Information	False - does not contain substances > 0.1 mass percentage
REACH Date	20221108
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Dati ambientali

Grado di protezione	IP30
Classe di protezione	Isolated (Class II)

Dimensioni

Larghezza in numero di intervalli modulari	48
Larghezza prodotto	1050 mm
Altezza prodotto	1100 mm
Profondità prodotto	160 mm
Larghezza campo	4
Peso netto prodotto	15.181 kg
Profondità integrata (t ₂)	0 mm
Diagramma dimensionale	2CPC000012D0201

Ordinazione

Unità imballo livello 1	pack 1 pezzo (i)
-------------------------	------------------

Peso lordo imballo livello 1	17.228 kg
------------------------------	-----------

Certificati e dichiarazioni (numero del documento)

Dichiarazione di conformità - CE	2CPC100012X0201
----------------------------------	-----------------

Installation

Istruzioni e manuali	No document needed
----------------------	--------------------

Download Piu' Usati

Scheda tecnica	2CPC000001C0101 2CPC000002C0101
----------------	------------------------------------

Classificazioni

ETIM 8	EC000214 - Small distribution board
ETIM 9	EC000214 - Small distribution board
Categoria RAEE	Prodotto non in ambito RAEE
CN8	Business To Consumer
Tipo di oggetto design	85381000
Codice classificazione oggetto	U

Categorie

Prodotti di bassa tensione → Quadri in metallo e centralini in plastica → Quadri per distribuzione secondaria → Compact Distribution Boards - Modules Assembled → ComfortLine Compact CA

