

WIRING DIAGRAM

P 1		P 2
1		1 WHITE
2		2 ORANGE
3		3 WHITE
6		6 GREEN
4		4 BLUE
5		5 WHITE
7		7 WHITE
8		8 BROWN
SH		SH

1. ELECTRICAL TEST:
   (1). 100% OPEN SHORT & MISS WIRE TEST;
   (2). INSULATION RESISTANCE:DC 250V 20M OHM MIN;
   (3). CONTACTOR RESISTANCE:30 OHM MAX
2. PRINTING:GHMT® roline CAT.6A U/UTP COMPONENT PATCH CORD LSZH 500MHz ISO/IEC 11801 & EN 50173-1 & ANSI/TIA-568-C.2
3. 100% Component Patch cord Test PASS
4. Minimum bending radius:60mm

COLOUR:Red(PANTONE:199C)

ITEM NO.	LENGTH(L)	TOLERANCE(T)
21.15.2982	300mm	±10mm
21.15.2710	500mm	±15mm
21.15.2711	1000mm	±30mm
21.15.2714	1500mm	±45mm
21.15.2712	2000mm	±60mm
21.15.2713	3000mm	±90mm
21.15.2715	5000mm	±150mm
21.15.2716	7500mm	±210mm
21.15.2717	10000mm	±300mm
21.15.2718	15000mm	±450mm
21.15.2719	20000mm	±600mm

ITEM NO.	21.15.2982	21.15.2710	21.15.2711	21.15.2712	21.15.2713
21.15.2714	21.15.2715	21.15.2716	21.15.2717	21.15.2718	21.15.2719
DESC.	ROLINE U/UTP PatchCord CAT.6A,LSOH,Comp.Level,red				

MATERIAL LIST

NO.	PARTS NAME	SPECIFICATION STANDARD	QT'Y	REMARK
⑥	LABEL	NO DRY GLUE LABEL	1PCS	
⑤	MINI TIE	PE MINI TIE(POSSESS METAL)	2PCS	
④	POLYETHYLENE BAG	POLYETHYLENE BAG	1PCS	
③	OVER MOLD	88A PVC Red	2PCS	
②	CONNECTOR	RJ45 8P8C'S UNSHIELDED PIN GOLD PLATED 3u", Transparent Blue	2PCS	
①	CABLE	S/FTP CAT.6A 26AWG (BC*1P+AL-FOIL)*4P+BRAID CABLE JACKET LSOH OD=6.2±0.2MM	1PCS	

BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.
		NEW	2016-09-13	A

SECOMP