







1. ELECTRICAL TEST:
   (1). 100% OPEN SHORT & MISS WIRE TEST;
   (2). INSULATION RESISTANCE:DC 250V 20M OHM MIN;
   (3). CONTACTOR RESISTANCE:30 OHM MAX
2. PRINTING:GHMT® roline CAT.6A S/FTP COMPONENT PATCH CORD LSZH 500MHz ISO/IEC 11801 & EN 50173-1 & ANSI/TIA-568-C.2
3. 100% Component Patch cord Test PASS
4. Minimum bending radius:60mm

COLOUR:yellow (PANTONE:135C)

ITEM NO.	LENGTH(L)	TOLERANCE(T)
21.15.2972	300mm	±10mm
21.15.2820	500mm	±15mm
21.15.2821	1000mm	±30mm
21.15.2824	1500mm	±45mm
21.15.2822	2000mm	±60mm
21.15.2823	3000mm	±90mm
21.15.2825	5000mm	±150mm
21.15.2826	7500mm	±210mm
21.15.2827	10000mm	±300mm
21.15.2828	15000mm	±450mm
21.15.2829	20000mm	±600mm

ITEM NO.	21.15.2972	21.15.2820	21.15.2821	21.15.2822	21.15.2823
21.15.2824	21.15.2825	21.15.2826	21.15.2827	21.15.2828	21.15.2829
DESC.	ROLINE S/FTP PatchCord CAT.6A,LSOH,Comp.Level,yellow				

MATERIAL LIST

NO.	PARTS NAME	SPECIFICATION STANDARD	QT'Y	REMARK
⑥	LABEL	NO DRY GLUE LABEL	1PCS	
⑤	MINI TIE	PE MINI TIE(POSSESS METAL)	2PCS	
④	POLYETHYLENE BAG	POLYETHYLENE BAG	1PCS	
③	OVER MOLD	88A PVC yellow	2PCS	
②	CONNECTOR	RJ45 8P8C'S SHIELDED PIN GOLD PLATED 3u″,SHELL PLATED NICKEL Transparent Blue	2PCS	
①	CABLE	S/FTP CAT.6A 26AWG (BC*1P+AL-FOIL)*4P+BRAID CABLE JACKET LSOH OD=6.2±0.2MM	1PCS	

BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.
		NEW	2016-09-13	A

SECOMP