

Installationsrohre
Halogenfrei

Tubes d'installation
Sans halogène

Installation tubes
Halogen free

PLICA-HALOFLEX



30.025.020_a



30.025.020_b

MAT

Spezialkunststoff
Matière synthétique spéciale
Special plastic material

TEMP

-5°C – +105°C



selbstverlöschend V0 UL94
auto-extinguible V0 UL94
self-extinguishing V0 UL94

HALO

halogenfrei
sans halogène
halogen free



750 N / 50 mm



2.0 kg / 10 cm / -5°C



isolierend
isolant
insulating

NORM

EN 61386-2-2
3323



PLICA-HALOFLEX

Halogenfreies Kunststoff-Isolierrohr aus Spezialkunststoff. Sehr flexibel. Verwendbar für halogenfreie Installationen.

PLICA-HALOFLEX

Tube sans halogène en matière synthétique spéciale. Très flexible. A utiliser pour installations libre de halogène.

PLICA-HALOFLEX

Tube halogen-free, special plastic material. Very flexible. To be used for halogen-free installations.

NORM metr.	 mm	 mm		Plica-Nr.	E-Nr.	VE
M16	16.0	11.5		14.8005.016	125 075 109	100
M20	20.0	14.8		14.8005.020	125 075 209	100
M25	25.0	18.3		14.8005.025	125 075 309	50
M32	32.0	24.3		14.8002.532	125 075 409	50
M40	40.0	29.4		14.8002.540	125 075 509	25
M50	50.0	37.5		14.8002.550	125 075 609	25
M63	63.0	47.4		14.8002.563	125 075 709	25

Technische Änderungen vorbehalten – Sous réserve de changements techniques – Technical alterations reserved

