

Installationsrohre
Starr

Tubes d'installation
Rigide

Installation tubes
Rigid

PLICA KIR K



30.020.010_a



30.020.010_b

MAT

PVC hart
CPV dur
PVC hard



IP 40

TEMP

-5°C – +60°C



nicht ausbreitend
non propagateur
no propagator



750 N



1.0 kg / 10 cm / -5°C



isolierend
isolant
insulating

NORM

EN 61386-2-1
3221

IMQ



Kunststoffisolerrohr PLICA-KIR K

Kaltbiegbar bis M25.

Tube isolant PLICA-TIT K

Cintrage à froid jusqu'à M25.

Installation tube PLICA KIR K

Cold bendable until M25.

NORM metr.	 mm	 mm			Plica-Nr.	E-Nr.	VE
Stangen à 3 m			Barres de 3 m	Lenghts of 3 m			
M16	16.0	13.0			10.1105.116	125 001 109	102
					10.4005.111	125 001 108	102
M20	20.0	16.9			10.1105.120	125 001 209	102
M25	25.0	21.4			10.1105.125	125 001 309	60
M32	32.0	27.8			10.1104.532	125 001 409	45
M40	40.0	35.4			10.1103.040	125 001 509	30
M50	50.0	44.3			10.1101.550	125 001 609	15
M63	63.0	56.5			10.1101.563	125 001 709	15
Stangen à 2 m			Barres de 2 m	Lenghts of 2 m			
M16	16.0	13.0			10.1123.416	125 001 109	34
M20	20.0	16.9			10.1123.420	125 001 209	34
M25	25.0	21.4			10.1122.025	125 001 309	20

Technische Änderungen vorbehalten – Sous réserve de changements techniques – Technical alterations reserved