



Features

- Integrated LED highbay; Black aluminium housing; 26400Lm; 165 W; 160 Lm/W; 4000K; Drive current: 720mA; CRI 80; 85° beam angle; DALI dimmable; IP65; IK08; Lifespan L80:B50 90,000 hrs; (D x H) 370 x 163 mm; 1.5 m mains cable; 1.5 m control cable; 1.2 m chain length including hooks.

Product Overview

Product name	Granit IP65 DALI 26400lm 840 WB
Technology	LED
General application	Logistics & Industry
ETIM Class	EC001716
Fixture luminous flux (lm)	26400
Luminaire efficacy (lm/W)	160
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	85
Glare control	< 25
Photobiological Risk Group	RG1
Total power consumption (W)	165
Electrical protection	Class I
Dimmable	Yes
LED Flickering Rate	Low (6% - 20%)
Housing colour	RAL 9017 - Traffic black
IP rating	IP65
IK rating	IK08

Granit IP65 DALI 26400lm 840 WB 0039754

Product EAN number	5410288397542
Warranty	5 years

Data table

GENERAL DATA

Product name	Granit IP65 DALI 26400lm 840 WB
Technology	LED
General application	Logistics & Industry
Operating temperature range (°C)	-30°C - 50°C
ETIM Class	EC001716
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	26400
Luminaire efficacy (lm/W)	160
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	85
Distribution type	Symmetric
Glare control	< 25
Photobiological Risk Group	RG1

ELECTRICAL DATA

Total power consumption (W)	165
Mains voltage (V)	220-240V
Lamp power factor	0.95
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	15
Electrical protection	Class I
Control gear required	No

Granit IP65 DALI 26400lm 840 WB 0039754

No. Of switching cycles before premature failures	>100000
Dimmable	Yes
Drive current (mA)	720
Inrush Current (A)	58
Inrush Duration (µs)	198
Glow Wire Test (°C)	850
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Low (6% - 20%)
Max. Luminaires per 10A C Breaker	10
Max. Luminaires per 13A C Breaker	12
Max. Luminaires per 16A C Breaker	16
Max. Luminaires per 20A C Breaker	20
Max. Luminaires per 10A B Breaker	6
Max. Luminaires per 13A B Breaker	8
Max. Luminaires per 16A B Breaker	10
Max. Luminaires per 20A B Breaker	12
Mains surge immunity (differential mode -> L-N) (kV)	6
Mains surge immunity (common mode -> L/N - GND) (kV)	6

LIFETIME DATA

Lifespan L70 B50	90000
Lifespan L70 B20	90000
Lifespan L70 B10	90000
Lifespan L80 B50	90000
Lifespan L80 B20	82000
Lifespan L80 B10	77000
Lifespan L90 B50	44000
Lifespan L90 B20	40000
Lifespan L90 B10	37000

PHYSICAL DATA

Granit IP65 DALI 26400lm 840 WB 0039754

Housing colour	RAL 9017 - Traffic black
IP rating	IP65
IK rating	IK08
Nominal Product Height (mm)	163
Nominal Product Diameter (mm)	370
Weight (kg)	2.703

PACKAGING

Single packaging type	Carton
Product EAN number	5410288397542
Packaging single length / height (cm)	40.0
Packaging single width (cm)	40.0
Packaging single depth (cm)	14.5
DUN14 (outer)	05410288397542
Units per outer package	1
Packaging outer length / height (cm)	40.0
Packaging outer width (cm)	40.0
Packaging outer depth (cm)	14.5

SAFETY DATA

Optimal operating condition (°C)	-30-50
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No