



Features

- Integrated LED highbay; Black aluminium housing; 13000Lm; 80 W; 163 Lm/W; 4000K; Drive current: 410mA; CRI 80; 85° beam angle; 0-10V dimmable; IP65; IK08; Lifespan L80:B50 90,000 hrs; (D x H) 298 x 168 mm; 1.5 m mains cable; 1.5 m control cable; 1.2 m chain length including hooks.

Product Overview

Product name	Granit IP65 0-10V 13000lm 840 WB
Technology	LED
General application	Logistics & Industry
ETIM Class	EC001716
Fixture luminous flux (lm)	13000
Luminaire efficacy (lm/W)	163
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	85
Glare control	< 25
Photobiological Risk Group	RG1
Total power consumption (W)	80
Electrical protection	Class I
Dimmable	Yes
LED Flickering Rate	Low (6% - 20%)
Housing colour	RAL 9017 - Traffic black
IP rating	IP65
IK rating	IK08

Granit IP65 0-10V 13000lm 840 WB 0039733

Product EAN number	5410288397337
Warranty	5 years

Data table

GENERAL DATA

Product name	Granit IP65 0-10V 13000lm 840 WB
Technology	LED
General application	Logistics & Industry
Operating temperature range (°C)	-30°C - 50°C
ETIM Class	EC001716
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	13000
Luminaire efficacy (lm/W)	163
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	85
Distribution type	Symmetric
Glare control	< 25
Photobiological Risk Group	RG1

ELECTRICAL DATA

Total power consumption (W)	80
Mains voltage (V)	220-240V
Lamp power factor	0.95
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	20
Electrical protection	Class I
Control gear required	No

Granit IP65 0-10V 13000lm 840 WB 0039733

No. Of switching cycles before premature failures	>100000
Dimmable	Yes
Drive current (mA)	410
Inrush Current (A)	80
Inrush Duration (µs)	300
Glow Wire Test (°C)	850
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Low (6% - 20%)
Max. Luminaires per 10A C Breaker	5
Max. Luminaires per 13A C Breaker	6
Max. Luminaires per 16A C Breaker	9
Max. Luminaires per 20A C Breaker	11
Max. Luminaires per 10A B Breaker	3
Max. Luminaires per 13A B Breaker	7
Max. Luminaires per 16A B Breaker	5
Max. Luminaires per 20A B Breaker	6
Mains surge immunity (differential mode -> L-N) (kV)	6
Mains surge immunity (common mode -> L/N - GND) (kV)	6

LIFETIME DATA

Lifespan L70 B50	90000
Lifespan L70 B20	90000
Lifespan L70 B10	90000
Lifespan L80 B50	90000
Lifespan L80 B20	82000
Lifespan L80 B10	77000
Lifespan L90 B50	44000
Lifespan L90 B20	40000
Lifespan L90 B10	37000

PHYSICAL DATA

Granit IP65 0-10V 13000lm 840 WB 0039733

Housing colour	RAL 9017 - Traffic black
IP rating	IP65
IK rating	IK08
Nominal Product Height (mm)	168
Nominal Product Diameter (mm)	298
Weight (kg)	2.243

PACKAGING

Single packaging type	Carton
Product EAN number	5410288397337
Packaging single length / height (cm)	32.5
Packaging single width (cm)	32.5
Packaging single depth (cm)	14.5
DUN14 (outer)	05410288397337
Units per outer package	1
Packaging outer length / height (cm)	32.5
Packaging outer width (cm)	32.5
Packaging outer depth (cm)	14.5

SAFETY DATA

Optimal operating condition (°C)	-30-50
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No