


OptiClip 600 3000K C8 HO WH CC WHITE 0043004



Features

• OPTICLIP 600 3000K C8 HO WH CC WHITE is a high efficacy low glare luminaire with replaceable light engines for office and education applications. Ceiling recessed LED luminaire with white colour plastic optic, direct light distribution, luminaire dimensions: 595x595x20mm, Sylvania White body colour (RAL9016), IP20, IK07, Constant Current driver, low LED flicker (+/-5%), Warm White (3000K) LED Colour Temperature, 3925lm luminous flux, 33W power consumption, 119lm/W system efficacy, CRI>80, SDCM 3 (3-step MacAdam ellipse) LED Colour Consistency, UGR<17, Luminance at 65° < 2000 cd/m², lifespan: 62,000 hours L80B20, photobiological safety risk group 1. Electrical protection Class II. Glow wire test 850°C.


Product Overview

Product name	OptiClip 600 3000K C8 HO WH CC WHITE
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
General application	Education, Office
ETIM Class	EC002892
Fixture luminous flux (lm)	3925
Luminaire efficacy (lm/W)	119
Colour temperature (K)	3000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	80
Glare control	< 17
Photobiological Risk Group	RG1

OptiClip 600 3000K C8 HO WH CC WHITE 0043004


Total power consumption (W)	33
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	No
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5410288430041
Warranty	5 years

Photometry



OptiClip 600 3000K C8 HO WH CC WHITE 0043004

Technical drawings



Data table

GENERAL DATA

Product name	OptiClip 600 3000K C8 HO WH CC WHITE
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
General application	Education, Office
Operating temperature range (°C)	-20°C - 25°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC002892
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	3925
Luminaire efficacy (lm/W)	119
Colour temperature (K)	3000

OptiClip 600 3000K C8 HO WH CC WHITE 0043004

Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Rated Luminous Intensity (cd)	2352
Beam Angle (°)	80
Distribution type	Symmetric
Glare control	< 17
Photobiological Risk Group	RG1

ELECTRICAL DATA

Total power consumption (W)	33
Mains voltage (V)	220-240V~
Lamp power factor	0.98
THD (at 230 V, 50 Hz, full load, at 100% dimming level) $\leq$ xx.x %	10
Electrical protection	Class II
Control gear required	No
Control gear type	LED driver constant current
Transformer required	No
Dimmable	No
Drive current (mA)	900
Inrush Current (A)	16
Inrush Duration (μ s)	100
Glow Wire Test (°C)	850
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. Luminaires per 16A C Breaker	31
Max. Luminaires per 10A B Breaker	11
Max. Luminaires per 16A B Breaker	19

LIFETIME DATA

Lifespan L70 B50	100000
Lifespan L70 B20	98500
Lifespan L70 B10	96000

OptiClip 600 3000K C8 HO WH CC WHITE 0043004

Lifespan L80 B50	66500
Lifespan L80 B20	62500
Lifespan L80 B10	60500
Lifespan L90 B50	33500
Lifespan L90 B20	30500
Lifespan L90 B10	29000

PHYSICAL DATA

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Diffuser finish	Matt/satinized
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	595
Nominal Product Width (mm)	595
Nominal Product Height (mm)	20
Weight (kg)	2.8

PACKAGING

Single packaging type	Carton
Product EAN number	5410288430041
Packaging single length / height (cm)	60.0
Packaging single width (cm)	4.0
Packaging single depth (cm)	60.0
DUN14 (outer)	05410288430041
Units per outer package	1
Packaging outer length / height (cm)	60.0
Packaging outer width (cm)	4.0
Packaging outer depth (cm)	60.0

SAFETY DATA

Optimal operating condition (°C)	-20-25
Special purpose lamp	No
Dry applications use only	No

SYLVANIA

OptiClip 600 3000K C8 HO WH CC WHITE
0043004

Suitable for household illumination	No
-------------------------------------	----

Light your world