

OptiClip 1200 4000K C8 2L HO WH CC WHITE 0043002



Features

• OPTICLIP 1200 2L 4000K C8 HO WH CC WHITE is a high efficacy low glare luminaire with replaceable light engines for office and education applications. Ceiling recessed LED luminaire with white colour plastic optic, direct light distribution, luminaire dimensions: 1195x295x20mm, Sylvania White body colour (RAL9016), IP20, IK07, Constant Current driver, low LED flicker (+/-5%), Neutral White (4000K) LED Colour Temperature, 4500lm luminous flux, 34W power consumption, 132lm/W system efficacy, CRI>80, SDCM 3 (3-step MacAdam ellipse) LED Colour Consistency, UGR<18, Luminance at 65° < 2000 cd/m², lifespan: 62,000 hours L80B20, photobiological safety risk group 1. Electrical protection Class II. Glow wire test 850°C.


Product Overview

Product name	OptiClip 1200 4000K C8 2L HO WH CC WHITE
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
General application	Education, Office
ETIM Class	EC002892
Fixture luminous flux (lm)	4500
Luminaire efficacy (lm/W)	132
Colour temperature (K)	4000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	80
Glare control	< 18
Photobiological Risk Group	RG1


OptiClip 1200 4000K C8 2L HO WH CC WHITE
0043002

Total power consumption (W)	34
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	No
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5410288430027
Warranty	5 years

Photometry



Technical drawings



OptiClip 1200 4000K C8 2L HO WH CC WHITE 0043002

Data table

GENERAL DATA

Product name	OptiClip 1200 4000K C8 2L HO WH CC WHITE
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
General application	Education, Office
Operating temperature range (°C)	-20°C - 25°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC002892
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	4500
Luminaire efficacy (lm/W)	132
Colour temperature (K)	4000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Rated Luminous Intensity (cd)	2460
Beam Angle (°)	80
Distribution type	Symmetric
Glare control	< 18
Photobiological Risk Group	RG1

ELECTRICAL DATA

Total power consumption (W)	34
Mains voltage (V)	220-240V~
Lamp power factor	0.98

OptiClip 1200 4000K C8 2L HO WH CC WHITE 0043002

THD (at 230 V, 50 Hz, full load, at 100% dimming level) $\leq$ xx.x %	10
Electrical protection	Class II
Control gear required	No
Control gear type	LED driver constant current
Transformer required	No
Dimmable	No
Drive current (mA)	950
Inrush Current (A)	16
Inrush Duration (μ s)	100
Glow Wire Test ($^{\circ}$ C)	850
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. Luminaires per 16A C Breaker	31
Max. Luminaires per 10A B Breaker	11
Max. Luminaires per 16A B Breaker	19

LIFETIME DATA

Lifespan L70 B50	100000
Lifespan L70 B20	98500
Lifespan L70 B10	96000
Lifespan L80 B50	66500
Lifespan L80 B20	62500
Lifespan L80 B10	60500
Lifespan L90 B50	33500
Lifespan L90 B20	30500
Lifespan L90 B10	29000

PHYSICAL DATA

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Diffuser finish	Matt/satinized
Diffuser material	PC Polycarbonate

OptiClip 1200 4000K C8 2L HO WH CC WHITE 0043002

Nominal Product Length (mm)	1193
Nominal Product Width (mm)	293
Nominal Product Height (mm)	20
Weight (kg)	2.8

PACKAGING

Single packaging type	Carton
Product EAN number	5410288430027
Packaging single length / height (cm)	120.0
Packaging single width (cm)	4.0
Packaging single depth (cm)	30.0
DUN14 (outer)	05410288430027
Units per outer package	1
Packaging outer length / height (cm)	120.0
Packaging outer width (cm)	4.0
Packaging outer depth (cm)	30.0

SAFETY DATA

Optimal operating condition (°C)	-20-25
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No