

OptiClip 1200 3000K C8 2L HO WH DALI WHITE 0043007



Features

• OPTICLIP 1200 3000K C8 HO WH DALI WHITE is a high efficacy low glare luminaire with replaceable light engines for office and education applications. Ceiling recessed LED luminaire with white colour plastic optic, direct light distribution, luminaire dimensions: 1195x295x20mm, Sylvania White body colour (RAL9016), IP20, IK07, DALI Dimmable, low LED flicker (+/-5%), Warm White (3000K) LED Colour Temperature, 4250lm luminous flux, 34W power consumption, 125lm/W system efficacy, CRI>80, SDCM 3 (3-step MacAdam ellipse) LED Colour Consistency, UGR<17, Luminance at 65° < 2000 cd/m², lifespan: 62,000 hours L80B20, photobiological safety risk group 1. Electrical protection Class II. Glow wire test 850°C.


Product Overview

Product name	OptiClip 1200 3000K C8 2L HO WH DALI WHITE
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
General application	Education, Office
ETIM Class	EC002892
Fixture luminous flux (lm)	4250
Luminaire efficacy (lm/W)	125
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	80
Glare control	< 17
Photobiological Risk Group	RG1


OptiClip 1200 3000K C8 2L HO WH DALI WHITE
0043007

Total power consumption (W)	34
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	Yes
Minimum dimming level (%)	1
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	5410288430072
Warranty	5 years

Photometry



Technical drawings



OptiClip 1200 3000K C8 2L HO WH DALI WHITE 0043007

Data table

GENERAL DATA

Product name	OptiClip 1200 3000K C8 2L HO WH DALI WHITE
Technology	LED (3 SDCM)
Cap/Base	N/A
Housing	Steel
Mount	Ceiling recessed mounting
General application	Education, Office
Operating temperature range (°C)	-20°C - 25°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC002892
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	4250
Luminaire efficacy (lm/W)	125
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Rated Luminous Intensity (cd)	2546
Beam Angle (°)	80
Distribution type	Symmetric
Glare control	< 17
Photobiological Risk Group	RG1

ELECTRICAL DATA

Total power consumption (W)	34
Mains voltage (V)	220-240V~
Lamp power factor	0.98

OptiClip 1200 3000K C8 2L HO WH DALI WHITE 0043007

THD (at 230 V, 50 Hz, full load, at 100% dimming level) $\leq$ xx.x %	10
Electrical protection	Class II
Control gear required	No
Control gear type	LED driver constant current
Transformer required	No
Dimmable	Yes
Minimum dimming level (%)	1
Drive current (mA)	950
Inrush Current (A)	23
Inrush Duration (μ s)	200
Glow Wire Test ($^{\circ}$ C)	850
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. Luminaires per 10A C Breaker	23
Max. Luminaires per 13A C Breaker	31
Max. Luminaires per 16A C Breaker	38
Max. Luminaires per 20A C Breaker	48
Max. Luminaires per 10A B Breaker	14
Max. Luminaires per 13A B Breaker	19
Max. Luminaires per 16A B Breaker	23
Max. Luminaires per 20A B Breaker	29

LIFETIME DATA

Lifespan L70 B50	100000
Lifespan L70 B20	98500
Lifespan L70 B10	96000
Lifespan L80 B50	66500
Lifespan L80 B20	62500
Lifespan L80 B10	60500
Lifespan L90 B50	33500
Lifespan L90 B20	30500
Lifespan L90 B10	29000

PHYSICAL DATA

OptiClip 1200 3000K C8 2L HO WH DALI WHITE 0043007

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Diffuser finish	Matt/satinized
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	1193
Nominal Product Width (mm)	293
Nominal Product Height (mm)	20
Weight (kg)	2.8

PACKAGING

Single packaging type	Carton
Product EAN number	5410288430072
Packaging single length / height (cm)	120.0
Packaging single width (cm)	4.0
Packaging single depth (cm)	30.0
DUN14 (outer)	05410288430072
Units per outer package	1
Packaging outer length / height (cm)	120.0
Packaging outer width (cm)	4.0
Packaging outer depth (cm)	30.0

SAFETY DATA

Optimal operating condition (°C)	-20-25
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No