

KubiXx 4000K 19KLM WIDE DALI
0062121



Features

- Logistics and Industry high bay luminaire with wide optics to provide homogenous light distribution for open space areas. 19300 lumens, 110W, 175lm/W, 4000K, CRI80, wide beam optic, DALI2 dimmable, 3 step MacAdam ellipse, grey finish (RAL7012), Class 1, 220-240V, IP65, IK06


Product Overview

Product name	KubiXx 4000K 19KLM WIDE DALI
Technology	LED
Housing	Steel
Mount	Suspended
General application	Logistics & Industry
ETIM Class	EC001716
Fixture luminous flux (lm)	19300
Luminaire efficacy (lm/W)	175
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Photobiological Risk Group	RG1
Total power consumption (W)	110
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	Yes
Housing colour	Grey
IP rating	IP65
IK rating	IK06
Product EAN number	5410288621210
Warranty	5 years

KubiXx 4000K 19KLM WIDE DALI
0062121

Dimming method	DALI-2
----------------	--------

Photometry



Data table

GENERAL DATA

Product name	KubiXx 4000K 19KLM WIDE DALI
Technology	LED
Housing	Steel
Mount	Suspended
General application	Logistics & Industry
Operating temperature range (°C)	0°C...+50°C
ETIM Class	EC001716
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	19300
Luminaire efficacy (lm/W)	175
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80

KubiXx 4000K 19KLM WIDE DALI 0062121

Photobiological Risk Group	RG1
----------------------------	-----

ELECTRICAL DATA

Total power consumption (W)	110
Mains voltage (V)	220-240V
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	DALI-2
Drive current (mA)	800
Inrush Current (A)	65
Inrush Duration (µs)	268
Glow Wire Test (°C)	850
Energy Efficiency Class (A->G) of contained light source	B
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	5
Max. products per 13A C Breaker	7
Max. products per 16A C Breaker	8
Max. products per 20A C Breaker	10
Max. products per 10A B Breaker	3
Max. products per 13A B Breaker	4
Max. products per 16A B Breaker	5
Max. products per 20A B Breaker	6

PHYSICAL DATA

Housing colour	Grey
IP rating	IP65
IK rating	IK06
Nominal Product Length (mm)	330
Nominal Product Width (mm)	370
Nominal Product Height (mm)	94
Weight (kg)	4.9



KubiXx 4000K 19KLM WIDE DALI
0062121

PACKAGING

Single packaging type	Carton
Product EAN number	5410288621210
Packaging single length / height (cm)	48.0
Packaging single width (cm)	41.0
Packaging single depth (cm)	26.0
DUN14 (outer)	05410288621210
Units per outer package	1
Packaging outer length / height (cm)	48.0
Packaging outer width (cm)	41.0

SAFETY DATA

Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No