



Features

- Logistics and Industry high bay luminaire with aisle optics to provide homogenous light distribution for narrow (high racking) areas. 19700 lumens, 110W, 178lm/W, 4000K, CRI80, aisle beam optic. Fitted with a SylSmart Connecte sensor. 3 step MacAdam ellipse, grey finish (RAL7012), Class 1, 220-240V, IP65, IK06 (sensor IK03)


Product Overview

Product name	KubiXx 4000K 19KLM AISLE SSA
Technology	LED
Housing	Steel
Mount	Suspended
General application	Logistics & Industry
ETIM Class	EC001716
Fixture luminous flux (lm)	19700
Luminaire efficacy (lm/W)	178
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Photobiological Risk Group	RG1
Total power consumption (W)	110
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	Yes
Housing colour	Grey
IP rating	IP65
IK rating	IK06

KubiXx 4000K 19KLM AISLE SSA
0062150

Product EAN number	5410288621500
Warranty	5 years
Dimming method	SylSmart SSA

Photometry



Data table

GENERAL DATA

Product name	KubiXx 4000K 19KLM AISLE SSA
Technology	LED
Housing	Steel
Mount	Suspended
General application	Logistics & Industry
Operating temperature range (°C)	0°C...+50°C
ETIM Class	EC001716
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	19700
Luminaire efficacy (lm/W)	178
Colour temperature (K)	4000

KubiXx 4000K 19KLM AISLE SSA 0062150

Light colour	Neutral White
CRI (Ra)	80
Photobiological Risk Group	RG1

ELECTRICAL DATA

Total power consumption (W)	110
Mains voltage (V)	220-240V
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	SylSmart SSA
Drive current (mA)	800
Inrush Current (A)	56
Inrush Duration (µs)	277
Glow Wire Test (°C)	850
Energy Efficiency Class (A->G) of contained light source	B
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	5
Max. products per 13A C Breaker	6
Max. products per 16A C Breaker	8
Max. products per 20A C Breaker	10
Max. products per 10A B Breaker	3
Max. products per 13A B Breaker	4
Max. products per 16A B Breaker	5
Max. products per 20A B Breaker	6

PHYSICAL DATA

Housing colour	Grey
IP rating	IP65
IK rating	IK06
Nominal Product Length (mm)	412
Nominal Product Width (mm)	370

KubiXx 4000K 19KLM AISLE SSA 0062150

Nominal Product Height (mm)	94
Weight (kg)	4.9

PACKAGING

Single packaging type	Carton
Product EAN number	5410288621500
Packaging single length / height (cm)	48.0
Packaging single width (cm)	41.0
Packaging single depth (cm)	26.0
DUN14 (outer)	05410288621500
Units per outer package	1
Packaging outer length / height (cm)	48.0
Packaging outer width (cm)	41.0

SAFETY DATA

Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No