

ToLEDo GLS 806LM 840 B22 SL4

Code article 0030842

SYLVANIA



Compact and elegant design Suitable replacement for halogen, incandescent and compact fluorescent lamps Instant light at the flick of a switch Uniform light distribution Good colour rendering (CRI 80) Perfect for hotels, restaurants, lobbies, corridors, stairwells, reception areas Lower maintenance costs 12,000 hours average rated life

Atouts techniques

Dimensions (mm)



Photométrie

ToLEDo GLS 806LM 840 B22 SL4

Code article 0030842

SYLVANIA

Données générales

Nom du produit	ToLEDo GLS 806LM 840 B22 SL4
Technologie	LED
Lamp shape	Pear-shape
Cap/Base	B22
Lamp finish	Opal
Built in presence detector	NONE
Fixture rating	Open
General application	Residential & Consumer
Operating temperature range (°C)	-20°C...+40°C
Virtual assistant compatibility	N/A
ETIM Class	EC001959
Warranty	3 ans

Données optiques

Useful luminous flux (Φ_{use})	806
Température de couleur (K)	4000
Couleur de lumière	Cool White
IRC (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	150
Photobiological Risk Group	RG1

Caractéristiques électriques

Power consumption (W)	8
Wattage (W)	7
Equivalent watt (W)	60
Actuel (A)	0.06
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Control gear required	No
Type d'appareillage	LED driver constant current
No. Of switching cycles before premature failures	>50000
Dimmable	No
Dimming method	N/A
Courant d'appel (A)	6
Inrush Duration (μ s)	150
Lamp Energy Label (class)	F
Nominal Frequency (Hz)	50/60Hz

Durée de vie

Lifespan L70 B50	15000
------------------	-------

Données physiques

Housing colour	White
IP rating	IP20
Nominal Product Height (mm)	105
Nominal Product Diameter (mm)	60
Poids (kg)	0.087

ToLEDo GLS 806LM 840 B22 SL4

Code article 0030842

SYLVANIA

Emballage

Product EAN number	5410288308425
Longueur simple de l'emballage (cm)	21.0
Largeur simple de l'emballage (cm)	6.1
Packaging single depth (cm)	11.2
DUN14 (inner)	15410288308422
Units per outer package	6
Packaging outer length / height (cm)	37.7
Packaging outer width (cm)	21.6
Packaging outer depth (cm)	12.5

Sécurité

Condition de fonctionnement optimal (° C)	-20-40
Consignes de nettoyage en cas de bris	Not applicable
Lampe à objectif spécial	No
Utilisation pour applications sèches uniquement	Yes
Ne convient pas à l'éclairage résidentiel	Yes
Safety message	Not Suitable for totally enclosed fixtures