


Resisto GRP 1200 IP66 3400lm 840

Code article 0010314

SYLVANIA


PROTM



Resisto GRP, integrated LED weatherproof luminaire, with smooth body finish optimized for LEDs with flat diffuser, easy to handle. Stainless steel diffuser clips and fixing brackets for surface mounting. The luminaire benefits from a water and dust resistant GRP body and PMMA diffuser. 3400lm; 24W; 142lm/W; 4000K; SDCM<4; non dimmable; CRI80; IP66; IK02; Class I; 72,000hrs (L80B20) lifespan; 1174mm x 90mm x 120mm; D-mark.

Atouts techniques


Dimensions (mm)



Photométrie

Distance [m]	Cone diameter [m]	Beam angle [°]	Beam diameter [m]	Illuminance [lx]
0.5	1.95 1.40	62.3° 46.4°	433 196	433 495
1.0	3.89 2.79	62.3° 46.4°	1033 49	1033 152
1.5	5.84 4.19	62.3° 46.4°	489 211	489 211
2.0	7.78 5.59	62.3° 46.4°	285 121	285 121
2.5	9.73 6.98	62.3° 46.4°	186 81	186 81
3.0	11.67 8.38	62.3° 46.4°	110 49	110 49

Distance [m] Cone diameter [m] Illuminance [lx]
 — C0 - C180 (Half beam angle: 108.0°)
 — C90 - C270 (Half beam angle: 128.0°)



Resisto GRP 1200 IP66 3400lm 840

Code article 0010314

SYLVANIA

Données générales

Nom du produit	Resisto GRP 1200 IP66 3400lm 840
Technologie	LED
Cap/Base	N/A
Montage	Ceiling surface mounting
General application	Logistics & Industry
Operating temperature range (°C)	-20°C...+45°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC002892
Warranty	5 ans

Données optiques

Fixture luminous flux (lm)	3400
Luminaire efficacy (lm/W)	142
Température de couleur (K)	4000
Couleur de lumière	Neutral White
IRC (Ra)	80
Colour Variation Initial (SDCM)	SDCM4
Beam Angle (°)	120
Photobiological Risk Group	RG1

Caractéristiques électriques

Consommation électrique totale (W)	24
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	1
Electrical protection	Class I
No. Of switching cycles before premature failures	>150000
Dimmable	No
Dimming method	N/A
Drive current (mA)	250
Courant d'appel (A)	21.7
Inrush Duration (µs)	220
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	33
Max. products per 13A C Breaker	45
Max. products per 16A C Breaker	54
Max. products per 20A C Breaker	70
Max. products per 10A B Breaker	22
Max. products per 13A B Breaker	27
Max. products per 16A B Breaker	34
Max. products per 20A B Breaker	42

Durée de vie

Lifespan L70 B50	72000
Lifespan L80 B20	72000
Lifespan L90 B10	30000

Resisto GRP 1200 IP66 3400lm 840

Code article 0010314

SYLVANIA

Données physiques

Housing colour	Grey
IP rating	IP66
IK rating	IK02
Longueur (mm)	1174
Largeur (mm)	90
Nominal Product Height (mm)	120
Poids (kg)	1.873

Emballage

Product EAN number	5410288103143
Longueur simple de l'emballage (cm)	124.8
Largeur simple de l'emballage (cm)	10.7
Packaging single depth (cm)	8.5
DUN14 (inner)	05410288103143
Units per outer package	6
Packaging outer length / height (cm)	126.8
Packaging outer width (cm)	33.5
Packaging outer depth (cm)	20.1

Sécurité

Glow Wire Test (°C)	650
Condition de fonctionnement optimal (° C)	-20-45