



# SylSplash 1500 IP65 4300lm 840

Code article 0045967

**SYLVANIA**

## Données générales

Nom du produit	SylSplash 1500 IP65 4300lm 840
Technologie	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Montage	Ceiling surface mounting
Built in presence detector	NONE
General application	Logistics & Industry
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
Virtual assistant compatibility	N/A
ETIM Class	EC002892
Numéro virtuel FI	4278194
Warranty	3 ans

## Données optiques

Fixture luminous flux (lm)	4300
Luminaire efficacy (lm/W)	96
Température de couleur (K)	4000
Couleur de lumière	Cool White
IRC (Ra)	80
Colour Variation Initial (SDCM)	SDCM5
Beam Angle (°)	125
Distribution type	Diffuse
Photobiological Risk Group	RG0

## Caractéristiques électriques

Consommation électrique totale (W)	45
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.9
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	10
Electrical protection	Class II
Type d'appareillage	LED driver constant current
Dimmable	No
Dimming method	N/A
Drive current (mA)	110
Max. drive current (mA)	220
Drive current - Range (mA)	/ 220mA
Courant d'appel (A)	15
Inrush Duration (µs)	400
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	50/60Hz
Max. products per 16A C Breaker	16
Max. products per 10A B Breaker	8
Max. products per 13A B Breaker	12
Max. products per 16A B Breaker	16
Max. products per 20A B Breaker	20
Connectable conductor cross section - Min (mm <sup>2</sup> )	0.5
Connectable conductor cross section - Max (mm <sup>2</sup> )	0.5

# SylSplash 1500 IP65 4300lm 840

Code article 0045967

**SYLVANIA**

## Durée de vie

Lifespan L70 B50	30000
Lifespan L70 B20	30000
Lifespan L70 B10	30000
Lifespan L80 B50	30000
Lifespan L80 B20	26000
Lifespan L80 B10	21000
Lifespan L90 B50	20000
Lifespan L90 B20	13000
Lifespan L90 B10	11000

## Données physiques

Housing colour	White
IP rating	IP65
IK rating	IK04
Diffuser finish	Opal
Diffuser material	PC Polycarbonate
Longueur (mm)	1530
Largeur (mm)	53
Nominal Product Height (mm)	35
Poids (kg)	0.4

## Emballage

Product EAN number	5410288459677
Longueur simple de l'emballage (cm)	153.3
Largeur simple de l'emballage (cm)	3.7
Packaging single depth (cm)	5.5
DUN14 (inner)	15410288459674
Units per outer package	20
Packaging outer length / height (cm)	156.2
Packaging outer width (cm)	24.5
Packaging outer depth (cm)	21.5

## Sécurité

Glow Wire Test (°C)	650
Condition de fonctionnement optimal (° C)	-20-40