

SylFlood IP65 7000LM 840 Black

Code article 0090159

SYLVANIA

YourHome™



The streamlined, durable, lightweight die-cast aluminium body makes SylFlood a perfect choice for building facades, car parks, garages and construction areas. The product includes 1 m pre-wired stripped cable and fitting bracket for quick and easy installation and the universal mounting bracket allows wall or surface mounting with the possibility of vertical tilting. Black (RAL9017) housing, white reflector, 7000 lm, 58 W, 121 lm/W, 4000K, non dimmable, CRI>80, IP65, IK06, Class I, 151 x 193 x 30 mm (L x W x H). Weight: 0.665 kg.

Atouts techniques

Photométrie

Données générales

Nom du produit	SylFlood IP65 7000LM 840 Black
Technologie	LED
Cap/Base	N/A
Housing	Aluminium
Montage	Floor standing
Built in presence detector	NONE
General application	Retail
Operating temperature range (°C)	-20°C...+40°C
Virtual assistant compatibility	N/A
ETIM Class	EC001744
Warranty	3 ans

Données optiques

Fixture luminous flux (lm)	7000
Luminaire efficacy (lm/W)	121
Température de couleur (K)	4000
Couleur de lumière	Cool White
IRC (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	110
Distribution type	None
Photobiological Risk Group	RG1

SylFlood IP65 7000LM 840 Black

Code article 0090159

SYLVANIA

Caractéristiques électriques

Consommation électrique totale (W)	58
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.9
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	20
Electrical protection	Class I
Type d'appareillage	Not required
Dimmable	No
Dimming method	N/A
Drive current (mA)	236
Courant d'appel (A)	2
Inrush Duration (µs)	100
Energy Efficiency Class (A->G) of contained light source	D
Nominal Frequency (Hz)	50/60Hz
Max. products per 16A C Breaker	35
Max. products per 16A B Breaker	21
Connectable conductor cross section - Min (mm²)	1
Connectable conductor cross section - Max (mm²)	1

Durée de vie

Lifespan L70 B50	30000
Lifespan L80 B10	20000

Données physiques

Housing colour	Black
IP rating	IP65
IK rating	IK06
Diffuser finish	Transparent
Diffuser material	Glass
Finition réflecteur	Not Applicable
Longueur (mm)	196
Largeur (mm)	251
Nominal Product Height (mm)	33
Poids (kg)	0.74

Emballage

Product EAN number	5410288901596
Longueur simple de l'emballage (cm)	20.5
Largeur simple de l'emballage (cm)	4.5
Packaging single depth (cm)	18.0
DUN14 (inner)	15410288901593
Units per outer package	6
Packaging outer length / height (cm)	30.0
Packaging outer width (cm)	20.2
Packaging outer depth (cm)	20.0

Sécurité

Glow Wire Test (°C)	650
Condition de fonctionnement optimal (° C)	-20-40