

SYLPIPE L300 530LM 3CCT IP20

Artikelnummer 0090240

SYLVANIA

Your**Home**



LED T5 replacement batten, high output range: with efficiency up to 140 lum/watt, seamless linking (up to 10M), ideal for direct lighting such as under cabinet or in kitchens, 120 degree beam angle, includes on/off switch and colour switchable switch Warm White, Cool White or Daylight (3000K, 4000K, 6500K), includes 0.30m stripped cable, white polycarbonate body, includes standard and tilting brackets. Available in 5 lengths - 300mm, 600mm, 900mm, 1200mm and 1500mm. 30,000hrs lifetime. Additional accessories available - Connecting cables, cable with plug and additional brackets.

Technische Werte

Photometrie

Allgemeine Daten

Produktname	SYLPIPE L300 530LM 3CCT IP20
Technologie	LED
Sockel	N/A
Gehäuse	PC Polycarbonate
Allgemeine Anwendungsbereiche	Residential & Consumer, Retail
ETIM Klasse	EC000109
Garantie	3 Jahre

Optische Daten

Leuchtenlichtstrom (lm)	530
Systemeffizienz (lm/W)	133
Lichtfarbe	Warm White or Neutral White or Daylight
Farbwiedergabeindex (Ra)	80
Photobiological Risk Group	RG1

Elektrische Daten

Leistungsaufnahme gesamt (W)	4
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Leistungsfaktor der Lampe	0.5
Elektrische Schutzklasse	Class II
Dimmbar	No
Dimming method	N/A
Einschaltstrom (A)	5.5
Dauer Einschaltstrom (µs)	100
Energy Efficiency Class (A->G) of contained light source	C
Nennfrequenz (Hz)	50/60Hz
Connectable conductor cross section - Max (mm²)	0.75

SYLPIPE L300 530LM 3CCT IP20

Artikelnummer 0090240



Lifetime data

Lebensdauer - L70B50	30000
----------------------	-------

Physikalische Daten

IP Schutzart	IP20
IK Schutzart	IK03
Länge (mm)	294
Breite (mm)	24
Nominale Produkthöhe (mm)	35
Gewicht (kg)	0.065

Packaging

EAN Code	5410288902401
Einzelverpackung Länge (cm)	48.0
Einzelverpackung Breite (cm)	4.0
Einzelverpackung Tiefe (cm)	3.2
DUN 14 (außen)	15410288902408
Anzahl an Einheiten je Außenverpackung	40
Außenverpackung Länge (cm)	49.5
Außenverpackung Breite (cm)	22.5
Außenverpackung Tiefe (cm)	28.0