

START PANEL IP54 UGR19 TW 600x600 4300LM SSC

Code article 0042706

SYLVANIA

Données générales

| | |
|----------------------------------|--|
| Nom du produit | START PANEL IP54 UGR19 TW 600x600 4300LM SSC |
| Technologie | LED |
| Cap/Base | N/A |
| Housing | Steel |
| Montage | Ceiling recessed mounting |
| Built in presence detector | NONE |
| General application | Education, Hospitality, Logistics & Industry, Office |
| Operating temperature range (°C) | -10°C...+45°C |
| Virtual assistant compatibility | N/A |
| ETIM Class | EC002892 |
| Warranty | 5 ans |

Données optiques

| | |
|---------------------------------|----------------|
| Fixture luminous flux (lm) | 4320 |
| Luminaire efficacy (lm/W) | 114 |
| Colour Code | N/A |
| Couleur de lumière | Tuneable White |
| IRC (Ra) | 80 |
| Colour Variation Initial (SDCM) | SDCM3 |
| Beam Angle (°) | 85 |
| Distribution type | Symmetric |
| Glare control | < 19 |
| Photobiological Risk Group | RG0 |

Caractéristiques électriques

| | |
|--|--------------------------------|
| Consommation électrique totale (W) | 38 |
| Primary Supply/Product voltage - min (V) | 220.0 |
| Primary Supply/Product voltage - max (V) | 240.0 |
| Lamp power factor | 0.9 |
| THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x % | 15.0 |
| Electrical protection | Class II |
| Type d'appareillage | LED driver constant current |
| Dimmable | Yes |
| Dimming method | SylSmart SSC |
| Minimum dimming level (%) | 5 |
| Drive current (mA) | 900 |
| Courant d'appel (A) | 60 |
| Inrush Duration (µs) | 100 |
| Energy Efficiency Class (A->G) of contained light source | C |
| Nominal Frequency (Hz) | 50/60Hz |
| LED Flickering Rate | Ultra low (5% or less) |
| Max. products per 10A C Breaker | 22 |
| Max. products per 16A C Breaker | 35 |
| Max. products per 16A B Breaker | 35 |
| Connectable conductor cross section - Max (mm ²) | 1.5 |
| Durée de vie | |
| Lifespan L70 B50 | 100000 |
| Lifespan L80 B20 | 61000 |

START PANEL IP54 UGR19 TW 600x600 4300LM SSC

Code article 0042706

SYLVANIA

Données physiques

| | |
|-----------------------------|-------------------------|
| Housing colour | RAL 9003 - Signal white |
| IP rating | IP54/20 |
| IK rating | IK03 |
| Diffuser finish | Diffuse |
| Diffuser material | PS Polystyrene |
| Longueur (mm) | 595 |
| Largeur (mm) | 595 |
| Nominal Product Height (mm) | 35 |
| Poids (kg) | 1.92 |

Emballage

| | |
|--------------------------------------|----------------|
| Product EAN number | 5410288427065 |
| Longueur simple de l'emballage (cm) | 60.0 |
| Largeur simple de l'emballage (cm) | 3.8 |
| Packaging single depth (cm) | 68.5 |
| DUN14 (inner) | 15410288427062 |
| Units per outer package | 4 |
| Packaging outer length / height (cm) | 73.0 |
| Packaging outer width (cm) | 17.0 |
| Packaging outer depth (cm) | 65.0 |

Sécurité

| | |
|---|--------|
| Glow Wire Test (°C) | 650 |
| Condition de fonctionnement optimal (° C) | -10-45 |