

# ToLEDo GLS 470LM 827 B22 SL

Code article 0030831


**SYLVANIA**



Compact and elegant design  
Suitable replacement for halogen, incandescent and compact fluorescent lamps  
Instant light at the flick of a switch  
Uniform light distribution  
Good colour rendering (CRI 80)  
Perfect for hotels, restaurants, lobbies, corridors, stairwells, reception areas  
Lower maintenance costs  
15,000 hours average rated life

## Atouts techniques

### Dimensions (mm)



### Photométrie

# ToLEDo GLS 470LM 827 B22 SL

Code article 0030831

**SYLVANIA**

## Données générales

Nom du produit	ToLEDo GLS 470LM 827 B22 SL
Technologie	LED
Lamp shape	Pear-shape
Cap/Base	B22
Lamp finish	Opal
Built in presence detector	NONE
Fixture rating	Open
General application	Residential & Consumer
Operating temperature range (°C)	-20°C...+40°C
Virtual assistant compatibility	N/A
ETIM Class	EC001959
Warranty	3 ans

## Données optiques

Useful luminous flux ( $\Phi_{use}$ )	470
Température de couleur (K)	2700
Couleur de lumière	Homelight
IRC (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	150
Photobiological Risk Group	RG1

## Caractéristiques électriques

Power consumption (W)	4
Wattage (W)	4
Equivalent watt (W)	40
Actuel (A)	0.04
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Control gear required	No
Type d'appareillage	LED driver constant current
No. Of switching cycles before premature failures	>50000
Dimmable	No
Dimming method	N/A
Courant d'appel (A)	4.5
Inrush Duration ( $\mu$ s)	170
Lamp Energy Label (class)	E
Nominal Frequency (Hz)	50/60Hz

## Durée de vie

Lifespan L70 B50	15000
------------------	-------

## Données physiques

Housing colour	White
IP rating	IP20
Nominal Product Height (mm)	105
Nominal Product Diameter (mm)	60
Poids (kg)	0.022

# ToLEDo GLS 470LM 827 B22 SL

Code article 0030831

**SYLVANIA**

## Emballage

Product EAN number	5410288308319
Longueur simple de l'emballage (cm)	6.0
Largeur simple de l'emballage (cm)	6.0
Packaging single depth (cm)	11.2
DUN14 (inner)	15410288308316
Units per outer package	6
Packaging outer length / height (cm)	18.8
Packaging outer width (cm)	12.7
Packaging outer depth (cm)	12.5

## Sécurité

Condition de fonctionnement optimal (° C)	-20-40
Consignes de nettoyage en cas de bris	Not applicable
Lampe à objectif spécial	No
Utilisation pour applications sèches uniquement	Yes
Ne convient pas à l'éclairage résidentiel	Yes
Safety message	Not Suitable for totally enclosed fixtures