

# YOURHOME SYLSPIKE 600LM 3000K

Code article 0090194

**SYLVANIA**



Highlight your garden with our adjustable spike light, featuring a tiltable head for precise illumination. Available in warm white (3000K) and cool white (4000K), this IP65-rated light is perfect for flower beds, trees, and outdoor landscapes. With a durable design, a long 30,000-hour lifetime, and a 3-year warranty, it's built to shine in any weather

## Atouts techniques

### Photométrie

#### Données générales

Nom du produit	YOURHOME SYLSPIKE 600LM 3000K
Technologie	LED
Cap/Base	N/A
Housing	Aluminium
Montage	Other
Built in presence detector	NONE
General application	Residential & Consumer
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
Virtual assistant compatibility	N/A
ETIM Class	EC000758
Warranty	3 ans

#### Données optiques

Fixture luminous flux (lm)	600
Luminaire efficacy (lm/W)	90
Température de couleur (K)	3000
Couleur de lumière	Warm White
IRC (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	30
Distribution type	Symmetric
Photobiological Risk Group	RG1

# YOURHOME SYLSPIKE 600LM 3000K

Code article 0090194

**SYLVANIA**

## Caractéristiques électriques

Consommation électrique totale (W)	6.7
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.55
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	200
Electrical protection	Class I
Control gear required	No
Type d'appareillage	LED driver constant current
Dimmable	No
Dimming method	N/A
Courant d'appel (A)	9.12
Inrush Duration (µs)	100
Energy Efficiency Class (A->G) of contained light source	F
Nominal Frequency (Hz)	50/60Hz

## Durée de vie

Lifespan L70 B50 | 42000

## Données physiques

Housing colour	RAL 9005 - Jet black
IP rating	IP65
IK rating	IK05
Diffuser finish	Other
Diffuser material	None
Longueur (mm)	131
Largeur (mm)	60
Nominal Product Height (mm)	218
Poids (kg)	0.35

## Emballage

Product EAN number	5410288901947
Longueur simple de l'emballage (cm)	21.0
Largeur simple de l'emballage (cm)	10.5
Packaging single depth (cm)	6.5
DUN14 (inner)	15410288901944
Units per outer package	10
Packaging outer length / height (cm)	23.0
Packaging outer width (cm)	34.5
Packaging outer depth (cm)	23.0

## Sécurité

Glow Wire Test (°C)	650
Condition de fonctionnement optimal (°C)	-20-40