


RANA NEO 8800LM S 1500 830 DALI 2L WHITE

Code article 0054260

SYLVANIA


PROTM



Surface or Suspended LED luminaire with Micro Prismatic Optic, Direct Light Distribution, Luminaire Dimensions: 1447x187x56mm, White body colour, IP20, IK07, DALI Dimmable, Low LED flicker (+/-5%), Warm White (3000K) LED Colour Temperature, 8800lm, 71W, 123lm/W efficacy, CRI>80, 3 SDCM (3-step MacAdam ellipse) LED Colour Consistency, UGR<17, Luminance at 65° < 3000 cd/m2, Lifespan: 96,000 hours L80B20, Quick electrical connection with push-connectors in the luminaire, Glow Wire Test 850°C.

Atouts techniques

Dimensions (mm)



Photométrie

0.5	0.90 0.68	E(1°) E(2°) E(3°)	41.9° 34.4° 24.4°	23899 6902 8996		
1.0	1.79 1.37	E(1°) E(2°) E(3°)	41.9° 34.4° 24.4°	9512 2229 3975		
1.5	2.69 2.05	E(1°) E(2°) E(3°)	41.9° 34.4° 24.4°	2547 564 747		
2.0	3.59 2.74	E(1°) E(2°) E(3°)	41.9° 34.4° 24.4°	4481 1009 1359		
2.5	4.49 3.42	E(1°) E(2°) E(3°)	41.9° 34.4° 24.4°	6465 1439 1939		
3.0	5.39 4.11	E(1°) E(2°) E(3°)	41.9° 34.4° 24.4°	8465 1889 2589		
					</	

RANA NEO 8800LM S 1500 830 DALI 2L WHITE

Code article 0054260

SYLVANIA

Données générales

Nom du produit	RANA NEO 8800LM S 1500 830 DALI 2L WHITE
Technologie	LED
Cap/Base	N/A
Housing	Steel
Montage	Ceiling surface mounting, Suspended
General application	Education, Office
Operating temperature range (°C)	0°C...+25°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC002892
Warranty	5 ans

Données optiques

Fixture luminous flux (lm)	8800
Luminaire efficacy (lm/W)	124
Température de couleur (K)	3000
Couleur de lumière	Warm White
IRC (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Glare control	< 17
Photobiological Risk Group	RG0

Caractéristiques électriques

Consommation électrique totale (W)	74
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.95
Electrical protection	Class I
Control gear required	No
Type d'appareillage	LED driver constant current
Dimmable	Yes
Dimming method	DALI
Drive current (mA)	300
Courant d'appel (A)	29
Inrush Duration (µs)	180
Energy Efficiency Class (A->G) of contained light source	C, D(more than 1 Light Source)
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	21
Max. products per 13A C Breaker	28
Max. products per 16A C Breaker	36
Max. products per 20A C Breaker	45
Max. products per 10A B Breaker	13
Max. products per 13A B Breaker	17
Max. products per 16A B Breaker	22
Max. products per 20A B Breaker	27

Durée de vie

Lifespan L70 B50	100000
Lifespan L80 B20	96000

RANA NEO 8800LM S 1500 830 DALI 2L WHITE

Code article 0054260



Données physiques

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Diffuser finish	Opal
Diffuser material	PC Polycarbonate
Longueur (mm)	1440
Largeur (mm)	187
Nominal Product Height (mm)	47
Poids (kg)	3.9

Emballage

Product EAN number	5410288542607
Longueur simple de l'emballage (cm)	153.5
Largeur simple de l'emballage (cm)	6.5
Packaging single depth (cm)	21.0
DUN14 (inner)	05410288542607
Units per outer package	1
Packaging outer length / height (cm)	153.5
Packaging outer width (cm)	6.5
Packaging outer depth (cm)	21.0

Sécurité

Glow Wire Test (°C)	850
---------------------	-----