



# START Surface IP54 PIR 450-1800lm 830/840

Code article 0043407

**SYLVANIA**

## Données générales

Nom du produit	START Surface IP54 PIR 450-1800lm 830/840
Technologie	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Montage	Ceiling surface mounting
Built in presence detector	PIR
General application	Hospitality, Museums & Galleries
Operating temperature range (°C)	-20°C...+40°C
Virtual assistant compatibility	N/A, Amazon Alexa
ETIM Class	EC002892
Numéro virtuel FI	4279507
Warranty	5 ans

## Données optiques

Fixture luminous flux (lm)	1800
Luminaire efficacy (lm/W)	103
Couleur de lumière	Warm White or Neutral White
IRC (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	120
Distribution type	Symmetric
Photobiological Risk Group	RG1

## Caractéristiques électriques

Consommation électrique totale (W)	17.5
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.8
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	20
Electrical protection	Class II
Type d'appareillage	LED driver constant current
No. Of switching cycles before premature failures	>100000
Dimmable	No
Dimming method	N/A
Drive current (mA)	100
Courant d'appel (A)	3
Inrush Duration (µs)	100
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Low (6% - 20%)
Max. products per 10A C Breaker	72
Max. products per 13A C Breaker	93
Max. products per 16A C Breaker	117
Max. products per 20A C Breaker	143
Max. products per 10A B Breaker	43
Max. products per 13A B Breaker	56
Max. products per 16A B Breaker	69
Max. products per 20A B Breaker	86
Connectable conductor cross section - Max (mm <sup>2</sup> )	1.5

# START Surface IP54 PIR 450-1800lm 830/840

Code article 0043407

**SYLVANIA**

## Durée de vie

Lifespan L70 B50	120000
Lifespan L70 B20	120000
Lifespan L70 B10	120000
Lifespan L80 B50	105000
Lifespan L80 B20	95000
Lifespan L80 B10	89000
Lifespan L90 B50	51000
Lifespan L90 B20	47000
Lifespan L90 B10	44000

## Données physiques

Housing colour	RAL 9003 - Signal white
IP rating	IP54
IK rating	IK03
Diffuser finish	Opal
Diffuser material	PMMA Acrylic
Nominal Product Height (mm)	105
Nominal Product Diameter (mm)	300
Poids (kg)	0.602

## Emballage

Product EAN number	5410288434070
Longueur simple de l'emballage (cm)	32.4
Largeur simple de l'emballage (cm)	11.3
Packaging single depth (cm)	32.4
DUN14 (inner)	15410288434077
Units per outer package	6
Packaging outer length / height (cm)	70.3
Packaging outer width (cm)	34.3
Packaging outer depth (cm)	35.2

## Sécurité

Glow Wire Test (°C)	850
Condition de fonctionnement optimal (° C)	-20-40