

OptiClip 1200 4000K C8 2L HO WH CC WHITE

Code article 0043002

SYLVANIA

Données générales

Nom du produit	OptiClip 1200 4000K C8 2L HO WH CC WHITE
Technologie	LED
Cap/Base	N/A
Housing	Steel
Montage	Ceiling recessed mounting
Built in presence detector	NONE
Fixture rating	Enclosed
General application	Education, Office
Operating temperature range (°C)	-20°C...+25°C
Performance ambient temperature Tq (°C)	25
Virtual assistant compatibility	N/A
ETIM Class	EC002892
Warranty	5 ans

Données optiques

Fixture luminous flux (lm)	4500
Luminaire efficacy (lm/W)	132
Température de couleur (K)	4000
Couleur de lumière	Warm White
IRC (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Luminous Intensity (cd)	2460
Beam Angle (°)	78
Distribution type	Symmetric
Glare control	< 18
Photobiological Risk Group	RG1

Caractéristiques électriques

Consommation électrique totale (W)	34
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.98
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	10
Electrical protection	Class II
Control gear required	No
Type d'appareillage	LED driver constant current
Dimmable	No
Dimming method	N/A
Drive current (mA)	950
Courant d'appel (A)	35
Inrush Duration (µs)	200
Energy Efficiency Class (A->G) of contained light source	E, E(more than 1 Light Source)
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	19
Max. products per 13A C Breaker	24
Max. products per 16A C Breaker	31
Max. products per 20A C Breaker	39
Max. products per 10A B Breaker	11
Max. products per 16A B Breaker	19
Max. products per 20A B Breaker	23
Connectable conductor cross section - Max (mm ²)	1.5

Durée de vie

Lifespan L70 B50	100000
Lifespan L80 B20	62500

OptiClip 1200 4000K C8 2L HO WH CC WHITE

Code article 0043002

SYLVANIA

Données physiques

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP40/20
IK rating	IK07
Diffuser finish	Matt/satinized
Diffuser material	PC Polycarbonate
Longueur (mm)	1193
Largeur (mm)	293
Nominal Product Height (mm)	20
Poids (kg)	2.8

Emballage

Product EAN number	5410288430027
Longueur simple de l'emballage (cm)	120.0
Largeur simple de l'emballage (cm)	4.0
Packaging single depth (cm)	30.0
DUN14 (inner)	05410288430027
Units per outer package	1
Packaging outer length / height (cm)	120.0
Packaging outer width (cm)	4.0
Packaging outer depth (cm)	30.0

Sécurité

Glow Wire Test (°C)	850
Condition de fonctionnement optimal (° C)	-20-25