

ToLEDo AVANT T8 CCG L1500 2700LM 840 50K RL

Code article 0030243

SYLVANIA




Energy efficient and affordable LED T8 solution to replace conventional fluorescent T8 lamps Omni-directional uniform light distribution thanks to glass tube construction design, same as traditional fluorescent T8 tubes High lumen package - 2700lm High lumen efficacy - 150 lm/W Switching cycles - 200,000X Average life 50,000 hours lifespan Lamp length - 1500mm Wide beam angle High power factor Suitable for general illumination in offices, supermarkets, department stores, train stations, petrol stations, parking lots and maintenance free applications Suitable for operation with electromagnetic gears / CCG and direct mains operation (220-240V) 5-Year warranty

Atouts techniques

Dimensions (mm)

Photométrie



ToLEDo AVANT T8 CCG L1500 2700LM 840 50K RL

Code article 0030243

SYLVANIA

Données générales

Nom du produit	ToLEDo AVANT T8 CCG L1500 2700LM 840 50K RL
Technologie	LED
Lamp shape	Tube, double-ended
Cap/Base	G13
Lamp finish	Frosted/Coated
General application	Hospitality, Logistics & Industry, Residential & Consumer
Operating temperature range (°C)	-20°C...+55°C
Virtual assistant compatibility	N/A
ETIM Class	EC001959
Numéro virtuel FI	4941348
Warranty	5 ans

Données optiques

Useful luminous flux (Φ _{use})	2700
Température de couleur (K)	4000
Couleur de lumière	Cool White
IRC (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	170
Photobiological Risk Group	RG0

Caractéristiques électriques

Power consumption (W)	18
Wattage (W)	18
Actuel (A)	0.109
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.9
Control gear required	No
Dimmable	No
Courant d'appel (A)	14.9
Inrush Duration (µs)	60
Lamp Energy Label (class)	D

Durée de vie

Lifespan L70 B50	50000
------------------	-------

Données physiques

IP rating	IP20
Longueur (mm)	1499
Nominal Product Diameter (mm)	28
Poids (kg)	0.227

Emballage

Product EAN number	5410288302430
Longueur simple de l'emballage (cm)	155.2
Largeur simple de l'emballage (cm)	2.9
Packaging single depth (cm)	2.9
DUN14 (inner)	15410288302437
Units per outer package	10
Packaging outer length / height (cm)	160.7
Packaging outer width (cm)	22.5
Packaging outer depth (cm)	10.5

Sécurité

Condition de fonctionnement optimal (° C)	-20-55
Consignes de nettoyage en cas de bris	Not applicable
Lampe à objectif spécial	No
Ne convient pas à l'éclairage résidentiel	Yes
Safety message	Suitable for totally enclosed fixture