



Insaver Slim UGR19 IP44 205 2100lm 930 0030526

LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9003 - Signal white
IP rating	IP44/20
IK rating	IK07
Product EAN number	5410288305264
Warranty	5 years

Photometry



Technical drawings



Data table

GENERAL DATA

Product name	Insaver Slim UGR19 IP44 205 2100lm 930
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Hospitality, Office, Retail
Operating temperature range (°C)	-20°C...+40°C
ETIM Class	EC001744
Warranty	5 years

OPTICAL DATA

Fixture luminous flux (lm)	2100
Luminaire efficacy (lm/W)	105
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	90

Insaver Slim UGR19 IP44 205 2100lm 930 0030526

Colour Variation Initial (SDCM)	3
Beam Angle (°)	70
Distribution type	Symmetric
Glare control	< 19
Photobiological Risk Group	RG1

ELECTRICAL DATA

Total power consumption (W)	20
Mains voltage (V)	220-240V
Lamp power factor	0.9
THD (at 230 V, 50 Hz, full load, at 100% dimming level) \leq xx.x %	20.0
Electrical protection	Class II
Control gear required	No
Control gear type	LED driver constant current
Dimmable	No
Drive current (mA)	600
Glow Wire Test (°C)	850
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. Luminaires per 16A C Breaker	57
Max. Luminaires per 16A B Breaker	45

LIFETIME DATA

Lifespan L70 B50	100000
Lifespan L80 B20	76000
Lifespan L80 B10	70000
Lifespan L90 B10	35000

PHYSICAL DATA

Housing colour	RAL 9003 - Signal white
IP rating	IP44/20

Insaver Slim UGR19 IP44 205 2100lm 930 0030526

IK rating	IK07
Diffuser finish	Other
Diffuser material	None
Reflector finish	Silver
Nominal Product Height (mm)	60
Nominal Product Diameter (mm)	220
Cutout Dimensions (W x L in mm or Diameter in mm)	205
Weight (kg)	0.73

PACKAGING

Single packaging type	Carton
Product EAN number	5410288305264
Packaging single length / height (cm)	23.2
Packaging single width (cm)	23.2
Packaging single depth (cm)	8.0
DUN14 (outer)	15410288305261
Units per outer package	12
Packaging outer length / height (cm)	48.0
Packaging outer width (cm)	48.0
Packaging outer depth (cm)	26.0

SAFETY DATA

Optimal operating condition (°C)	-20-40
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No