

# START Downlight Flat 205 IP44 1750LM 840 DIM

Code article 0054123

**SYLVANIA**


**START**<sup>TM</sup>



START Downlight Flat IP44 DIM is an integrated LED recessed downlight with a separate, phase dimmable driver and loop in- out box, 17W; 1750Lm; 103Lm/W; 4000K; IP44 rated from the front.


## Atouts techniques

### Dimensions (mm)



### Photométrie

Distance [m]	Cone diameter [m]	Beam angle [°]	Illuminance [lx]
0.5	1.41 1.43	50° 54.7° 59.9°	2500 244 239
1.0	2.82 2.86	50° 54.7° 59.9°	631 61 61
1.5	4.24 4.30	50° 54.7° 59.9°	281 21 21
2.0	5.65 5.71	50° 54.7° 59.9°	155 16 16
2.5	7.06 7.14	50° 54.7° 59.9°	101 10 10
3.0	8.47 8.67	50° 54.7° 59.9°	71 7 7



# START Downlight Flat 205 IP44 1750LM 840 DIM

Code article 0054123

**SYLVANIA**

## Données générales

Nom du produit	START Downlight Flat 205 IP44 1750LM 840 DIM
Technologie	LED
Cap/Base	N/A
Housing	Aluminium
Montage	Ceiling recessed mounting
Built in presence detector	NONE
General application	Hospitality
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
Virtual assistant compatibility	N/A
ETIM Class	EC001744
Numéro virtuel FI	4278499
Warranty	5 ans

## Données optiques

Fixture luminous flux (lm)	1750
Luminaire efficacy (lm/W)	103
Température de couleur (K)	4000
Couleur de lumière	Cool White
IRC (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	120
Distribution type	Symmetric
Glare control	< 28
Photobiological Risk Group	RG0

## Caractéristiques électriques

Consommation électrique totale (W)	17
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.9
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	20.0
Electrical protection	Class II
Control gear required	No
Type d'appareillage	LED driver constant current
Dimmable	Yes
Dimming method	Mains: leading / trailing edge
Drive current (mA)	450
Courant d'appel (A)	4.16
Inrush Duration (µs)	112
Energy Efficiency Class (A->G) of contained light source	D
Nominal Frequency (Hz)	50Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	67
Max. products per 13A C Breaker	87
Max. products per 16A C Breaker	107
Max. products per 20A C Breaker	133
Max. products per 10A B Breaker	67
Max. products per 13A B Breaker	87
Max. products per 16A B Breaker	107
Max. products per 20A B Breaker	133
Connectable conductor cross section - Min (mm <sup>2</sup> )	0.75
Connectable conductor cross section - Max (mm <sup>2</sup> )	1.5

# START Downlight Flat 205 IP44 1750LM 840 DIM

Code article 0054123

**SYLVANIA**

## Durée de vie

Lifespan L70 B50	78000
Lifespan L80 B20	43000
Lifespan L80 B10	42000
Lifespan L90 B10	23000

## Données physiques

Housing colour	RAL 9003 - Signal white
IP rating	IP44/20
IK rating	IK06
Diffuser finish	Opal
Diffuser material	PS Polystyrene
Finition réflecteur	Not Applicable
Nominal Product Height (mm)	21
Nominal Product Diameter (mm)	226
Built-in diameter (mm)	205
Poids (kg)	0.546

## Emballage

Product EAN number	5410288541235
Longueur simple de l'emballage (cm)	25.3
Largeur simple de l'emballage (cm)	5.0
Packaging single depth (cm)	23.3
DUN14 (inner)	15410288541232
Units per outer package	10
Packaging outer length / height (cm)	53.3
Packaging outer width (cm)	27.3
Packaging outer depth (cm)	26.1

## Sécurité

Glow Wire Test (°C)	650
Condition de fonctionnement optimal (° C)	-20-40