

Pixo Line 1500 D Asym 830 Black

Code article 0007835

SYLVANIA


PROTM



Pixo Line is a linear track system, adds flexibility to any space due the variety of product options Offers an easy installation with two separate modules Push-in/push-out mechanism with GR6d-15 connector Compatible with Zhaga Book 14 Aluminium body, plastic end caps, traslucent double asymmetric optic diffuser, light beam angle:25° black finishing colour. Light color temperature: 3000K, max. system power: 50W Max. fixture lumen output: 7500lm, efficacy: 150lm/W, Ra80 typical, LED chromacity: 3 step MacAdam ellipse (SDCM3), IR/UV free light source without heat radiation Multipower driver module with 8 power settings meet all installation needs with one single product, selection and setting on driver - between 17W (350mA), 19W (400mA), 24W (500mA), 29W (600mA), 34W (700mA), 38W (800mA), 43W (900mA), 50W (1050mA) Suitable for installation on 3-circuit tracks, please check compatibility list on the instruction sheet. Compatible with OneTrack Electrical protection: Class III. Degree of protection: IP20, suitable for indoor environment only Light modules should be combined with suitable in-track drivers Nominal product dimensions: L.1464mmx38.4mmx37mm

Atouts techniques

Dimensions (mm)



Photométrie

Distance [m]	Cone diameter [m]	Beam diameter [m]	Illuminance [lx]
0.5	0.83 2.48	E10°: 38.7° E30°: 26.6° E60°: 11.4°	621 266 114
1.0	1.66 4.96	E10°: 38.7° E30°: 26.6° E60°: 11.4°	156 61 25
1.5	2.49 7.43	E10°: 38.7° E30°: 26.6° E60°: 11.4°	470 188 73
2.0	3.32 9.90	E10°: 38.7° E30°: 26.6° E60°: 11.4°	288 114 45
2.5	4.15 12.38	E10°: 38.7° E30°: 26.6° E60°: 11.4°	170 68 27
3.0	4.98 14.85	E10°: 38.7° E30°: 26.6° E60°: 11.4°	118 47 18

Distance [m] Cone diameter [m] Illuminance [lx]
 — C2 - C180 (Half beam angle: 136.0°)
 — C50 - C270 (Half beam angle: 79.4°)

Pixo Line 1500 D Asym 830 Black

Code article 0007835

SYLVANIA

Données physiques

Housing colour	Black
IP rating	IP20
IK rating	IK03
Longueur (mm)	1464
Largeur (mm)	37
Nominal Product Height (mm)	38.4
Poids (kg)	0.9

Emballage

Product EAN number	5410288078359
Longueur simple de l'emballage (cm)	147.0
Largeur simple de l'emballage (cm)	4.3
Packaging single depth (cm)	4.3
DUN14 (inner)	15410288078356
Units per outer package	10
Packaging outer length / height (cm)	149.0
Packaging outer width (cm)	24.0
Packaging outer depth (cm)	11.0

Sécurité

Glow Wire Test (°C)	650
Condition de fonctionnement optimal (° C)	-20-40