



# Nilo 800 Direct/Indirect 3000K DALI EM Black

Code article 2050606

Concord

## Données générales

|                                  |  |
|----------------------------------|--|
| Nom du produit                   | Nilo 800 Direct/Indirect 3000K DALI EM Black |
| Technologie                      | LED  |
| Cap/Base                         | N/A  |
| Housing                          | Aluminium                                    |
| Montage                          | Suspended                                    |
| Built in presence detector       | NONE   |
| General application              | Hospitality, Museums & Galleries, Retail     |
| Operating temperature range (°C) | 1°C...+25°C                                  |
| Virtual assistant compatibility  | N/A  |
| ETIM Class                       | EC002892                                     |
| Warranty                         | 5 ans  |

## Données optiques

|                                 |            |
|---------------------------------|------------|
| Fixture luminous flux (lm)      | 5700       |
| Luminaire efficacy (lm/W)       | 102        |
| Température de couleur (K)      | 3000       |
| Couleur de lumière              | Warm White |
| IRC (Ra)                        | 80         |
| Colour Variation Initial (SDCM) | SDCM3      |
| Distribution type               | Symmetric  |
| Glare control                   | < 23       |
| Photobiological Risk Group      | RG0        |
| Emergency duration (h)          | 3          |

## Caractéristiques électriques

|  |                             |
|--|-----------------------------|
| Consommation électrique totale (W)                               | 56                          |
| Primary Supply/Product voltage - min (V)                         | 220.0                       |
| Primary Supply/Product voltage - max (V)                         | 240.0                       |
| Lamp power factor  | 0.98                        |
| THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x % | 5.0                         |
| Electrical protection  | Class I                     |
| Type d'appareillage  | LED driver constant current |
| Dimmable   | Yes                         |
| Dimming method   | DALI                        |
| Drive current (mA)   | 1280                        |
| Courant d'appel (A)  | 23                          |
| Inrush Duration (µs)   | 200                         |
| Energy Efficiency Class (A->G) of contained light source         | C                           |
| Nominal Frequency (Hz)   | 50/60Hz                     |
| Max. products per 10A C Breaker                                  | 23                          |
| Max. products per 13A C Breaker                                  | 31                          |
| Max. products per 16A C Breaker                                  | 38                          |
| Max. products per 16A B Breaker                                  | 23                          |
| Connectable conductor cross section - Max (mm <sup>2</sup> )     | 2.5                         |

## Durée de vie

Lifespan L80 B20 | 50000

## Données physiques

|                               |              |
|-------------------------------|--------------|
| Housing colour                | Black        |
| IP rating                     | IP20         |
| IK rating                     | IK03         |
| Diffuser finish               | Opal         |
| Diffuser material             | PMMA Acrylic |
| Nominal Product Height (mm)   | 65           |
| Nominal Product Diameter (mm) | 800          |
| Poids (kg)                    | 4.9          |

# Nilo 800 Direct/Indirect 3000K DALI EM Black

Code article 2050606

**Concord**

## Emballage

|                                      |                |
|--------------------------------------|----------------|
| Product EAN number                   | 5025768506064  |
| Longueur simple de l'emballage (cm)  | 87.0           |
| Largeur simple de l'emballage (cm)   | 87.0           |
| Packaging single depth (cm)          | 10.0           |
| DUN14 (inner)                        | 05025768506064 |
| Units per outer package              | 1              |
| Packaging outer length / height (cm) | 87.0           |
| Packaging outer width (cm)           | 87.0           |
| Packaging outer depth (cm)           | 10.0           |

## Sécurité

|   |      |
|---|------|
| Glow Wire Test (°C)                       | 650  |
| Condition de fonctionnement optimal (° C) | 1-25 |