

START Surface IP44 2050lm MW 830/840 DualTone

Code article 0043436

SYLVANIA

Données générales

Nom du produit	START Surface IP44 2050lm MW 830/840 DualTone
Technologie	LED
Cap/Base	N/A
Housing	Steel
Montage	Ceiling surface mounting
Built in presence detector	MICROWAVE
General application	Hospitality
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
Virtual assistant compatibility	N/A
ETIM Class	EC002892
Warranty	3 ans

Données optiques

Fixture luminous flux (lm)	2050
Luminaire efficacy (lm/W)	85
Couleur de lumière	Warm White or Neutral White
IRC (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	120
Distribution type	Diffuse
Photobiological Risk Group	RG0

Caractéristiques électriques

Consommation électrique totale (W)	24
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.7
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	70
Electrical protection	Class I
Type d'appareillage	LED driver constant current
Dimmable	No
Dimming method	N/A
Drive current (mA)	74
Courant d'appel (A)	2
Inrush Duration (µs)	30
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	50Hz
LED Flickering Rate	High (>40%)
Max. products per 10A C Breaker	15
Max. products per 13A C Breaker	20
Max. products per 16A C Breaker	24
Max. products per 20A C Breaker	30
Max. products per 10A B Breaker	15
Max. products per 13A B Breaker	20
Max. products per 16A B Breaker	24
Max. products per 20A B Breaker	30
Connectable conductor cross section - Max (mm ²)	2.5

Durée de vie

Lifespan L70 B50	90000
Lifespan L80 B50	90000
Lifespan L90 B50	50000

START Surface IP44 2050lm MW 830/840 DualTone

Code article 0043436

SYLVANIA

Données physiques

Housing colour	White
IP rating	IP44
IK rating	IK03
Diffuser finish	Opal
Diffuser material	Polypropylene
Nominal Product Height (mm)	100
Nominal Product Diameter (mm)	360
Poids (kg)	0.548

Emballage

Product EAN number	5410288434360
Longueur simple de l'emballage (cm)	36.3
Largeur simple de l'emballage (cm)	10.2
Packaging single depth (cm)	36.5
DUN14 (inner)	15410288434367
Units per outer package	6
Packaging outer length / height (cm)	66.3
Packaging outer width (cm)	40.9
Packaging outer depth (cm)	41.4

Sécurité

Glow Wire Test (°C)	650
Condition de fonctionnement optimal (° C)	-20-40