


DELTAWING 1200 4K EM

Code article 0042934

SYLVANIA


PROTM



DELTAWING 1200 4K EM is a ceiling and wall surface, suspended LED luminaire with opal diffuser, 1160x160x60mm dimensions, 38W system power, 4,600lm flux and 121lm/W efficacy, CRI (Ra) >80, 4000K (Neutral White) CCT, chromaticity tolerance of 3-step MacAdam ellipse, Constant Current (4-steps DIP switch) driver and 3hrs emergency with LiFePO4 battery, RAL9003 finishing, L70B50 100khrs / L80B50 80khrs lifespan, IK06 impact resistance, IP44 ingress protection rating (in ceiling surface installation), Electrical protection Class I, Glow wire test 850°C.

Atouts techniques

Dimensions (mm)




Photométrie

Distance [m]	Cone diameter [m]	Beam angle [°]	Beam diameter [m]	Beam diameter [ft]
0.5	1.35	152°	1.35	4.43
1.0	2.69	152°	2.69	8.83
1.5	4.04	152°	4.04	13.25
2.0	5.39	152°	5.39	17.68
2.5	6.73	152°	6.73	22.11
3.0	8.08	152°	8.08	26.54

Distance [m] Cone diameter [m]
C0 - C180 (half beam angle: 113.2°)
C90 - C270 (half beam angle: 106.8°)

Illuminance [lx]



DELTAWING 1200 4K EM

Code article 0042934

SYLVANIA

Données générales

Nom du produit	DELTAWING 1200 4K EM
Technologie	LED
Cap/Base	N/A
Housing	PC Polycarbonate, Steel
Montage	Ceiling surface mounting, Wall surface mounted
Built in presence detector	NONE
General application	Education, Office, Logistics & Industry
Operating temperature range (°C)	-20°C...+40°C
Virtual assistant compatibility	N/A
ETIM Class	EC002892
Warranty	5 ans

Données optiques

Fixture luminous flux (lm)	4600
Luminaire efficacy (lm/W)	121
Température de couleur (K)	4000
Couleur de lumière	Neutral White
IRC (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	120
Distribution type	Symmetric
Photobiological Risk Group	RG0
Emergency duration (h)	3

Caractéristiques électriques

Consommation électrique totale (W)	38
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.9
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	20
Electrical protection	Class I
Type d'appareillage	LED driver constant current
Dimmable	No
Dimming method	N/A
Drive current (mA)	350
Courant d'appel (A)	30
Inrush Duration (µs)	190
Energy Efficiency Class (A->G) of contained light source	D
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	22
Max. products per 16A C Breaker	35
Max. products per 16A B Breaker	35
Connectable conductor cross section - Max (mm²)	1.5

Durée de vie

Lifespan L70 B50	100000
Lifespan L80 B20	80000

DELTAWING 1200 4K EM

Code article 0042934

SYLVANIA

Données physiques

Housing colour	RAL 9003 - Signal white
IP rating	IP44
IK rating	IK06
Diffuser finish	Diffuse
Diffuser material	PC Polycarbonate
Longueur (mm)	1160
Largeur (mm)	160
Nominal Product Height (mm)	60
Poids (kg)	1.965

Emballage

Product EAN number	5410288429342
Longueur simple de l'emballage (cm)	124.6
Largeur simple de l'emballage (cm)	16.5
Packaging single depth (cm)	6.6
DUN14 (inner)	15410288429349
Units per outer package	4
Packaging outer length / height (cm)	126.0
Packaging outer width (cm)	34.5
Packaging outer depth (cm)	15.2

Sécurité

Glow Wire Test (°C)	850
Condition de fonctionnement optimal (° C)	-20-40