

IR Quattro HD 24m

V3 KNX - concealed black
 EAN 4007841 068622
 Article number 068622



infrared sensor
360°



max. 8 x 8 m
presence

HD

4800 zones

KNX®

KNX 4 channel



ideal 2,5 - 10 m



indoor sensor

iQ

iQ-mode



energy saving

5 years

manufacturer's
warranty steinel-
professional.de/
garantie

CE

CE

Function description

Detection no finer! Infrared presence detector Presence Control PRO IR Quattro HD KNX for indoors, ideal for medium to large-size offices, conference and meeting rooms, classrooms and lecture theatres, sports halls and warehouses, installation height up to 10 m, with digital BUS interface for controlling 4 lighting channels and HVAC, 4800 switching zones for the ultimate in detection quality, presence detection over a true 64 m², square detection zone, mechanically scalable.

Technical specifications

Dimensions (L x W x H)	69 x 120 x 120 mm	Optimum mounting height	2,8 m
With motion detector	Yes	Detection angle	360 °
Manufacturer's Warranty	5 years	Angle of aperture	160 °
Settings via	ETS software, Remote control, Bus, Smart Remote	Sneak-by guard	Yes
With remote control	No	Capability of masking out individual segments	No
Version	KNX - concealed black	Electronic scalability	No
PU1, EAN	4007841068622	Mechanical scalability	Yes
Type	Presence detector	Reach, radial	8 x 8 m (64 m ²)
Application, place	Indoors	Reach, tangential	20 x 20 m (400 m ²)
Application, room	classroom, lecture hall, open-plan office, high-bay warehouse, production facilities, conference room / meeting room, duty room, recreation room, changing room, sports hall, reception / lobby, multi-storey / underground car park, Indoors	Reach, presence	8 x 8 m (64 m ²)
Colour	black	Switching zones	4800 switching zones
		Twilight setting	10 – 1000 lx
		Time setting	10 s – 1092 Min.
		Basic light level function	Yes
		Basic light level function time	Permanently ON, 1-255 min, all night

IR Quattro HD 24m

V3 KNX - concealed black
 EAN 4007841 068622
 Article number 068622

Technical specifications


Colour, RAL	9005
Includes corner wall mount	No
Installation site	ceiling
Installation	Concealed wiring, Ceiling
IP-rating	IP20
Protection class	II
Ambient temperature	-25 – 55 °C
Material	Plastic
Power supply, detail	KNX bus
With bus coupling	Yes
Sensor Technology	Passive infrared
Mounting height	2,50 – 10,00 m
Mounting height max.	10,00 m

Main light adjustable	0 - 100 %
Twilight setting TEACH	Yes
Constant-lighting control	Yes
KNX functions	Photo-cell controller, Basic light level function, Light level, HVAC output, Constant-lighting control, Light output 4x, Presence output, Day / night function, Logic gate
Interconnection	Yes
Type of interconnection	Master/master, Master/slave
Interconnection via	KNX bus
Rated current	10 mA

Accessories

EAN 4007841 593018	Service remote control RC6 KNX
EAN 4007841 003036	Control PRO guard cage
EAN 4007841 009151	Remote control Smart Remote
EAN 4007841 592912	User remote control RC7 KNX

Detection Zone



Mögliche Montagehöhe: 2,50 m – 10,00 m
 Orange: Präsenz
 Schwarz: tangential

Dimension Drawing

