

DELTAWING 1200 4K MW

Code article 0042939

SYLVANIA

Données générales

Nom du produit	DELTAWING 1200 4K MW
Technologie	LED
Cap/Base	N/A
Housing	PC Polycarbonate, Steel
Montage	Ceiling surface mounting, Wall surface mounted
Built in presence detector	MICROWAVE
General application	Education, Office, Logistics & Industry
Operating temperature range (°C)	-20°C...+40°C
Virtual assistant compatibility	N/A
ETIM Class	EC002892
Numéro virtuel FI	4279351
Warranty	5 ans

Données optiques

Fixture luminous flux (lm)	4600
Luminaire efficacy (lm/W)	131
Température de couleur (K)	4000
Couleur de lumière	Neutral White
IRC (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	120
Distribution type	Symmetric
Photobiological Risk Group	RG0

Caractéristiques électriques

Consommation électrique totale (W)	35
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.9
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	10
Electrical protection	Class I
Type d'appareillage	LED driver constant current
Dimmable	Yes
Dimming method	N/A
Drive current (mA)	350
Courant d'appel (A)	28.8
Inrush Duration (µs)	192
Energy Efficiency Class (A->G) of contained light source	D
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	23
Max. products per 16A C Breaker	39
Max. products per 16A B Breaker	23
Connectable conductor cross section - Max (mm ²)	1.5

Durée de vie

Lifespan L70 B50	100000
Lifespan L80 B50	90000
Lifespan L80 B20	80000
Lifespan L80 B10	70000
Lifespan L90 B50	38000
Lifespan L90 B20	36000
Lifespan L90 B10	34000

DELTAWING 1200 4K MW

Code article 0042939

SYLVANIA

Données physiques

Housing colour	RAL 9003 - Signal white
IP rating	IP44
IK rating	IK06
Diffuser finish	Diffuse
Diffuser material	PC Polycarbonate
Longueur (mm)	1160
Largeur (mm)	160
Nominal Product Height (mm)	60
Poids (kg)	1.965

Emballage

Product EAN number	5410288429397
Longueur simple de l'emballage (cm)	124.6
Largeur simple de l'emballage (cm)	16.5
Packaging single depth (cm)	6.6
DUN14 (inner)	15410288429394
Units per outer package	4
Packaging outer length / height (cm)	126.0
Packaging outer width (cm)	34.5
Packaging outer depth (cm)	15.2

Sécurité

Glow Wire Test (°C)	850
Condition de fonctionnement optimal (° C)	-20-40