

AREUM SUSPENDED 1500 D/I 4000K DALI EM ALU

Code article 0042966

SYLVANIA

Données générales

| | |
|----------------------------------|--|
| Nom du produit | AREUM SUSPENDED 1500 D/I 4000K DALI EM ALU |
| Technologie | LED |
| Cap/Base | N/A |
| Housing | Aluminium, Steel |
| Montage | Suspended |
| Built in presence detector | NONE |
| General application | Office |
| Operating temperature range (°C) | 5°C...+35°C |
| Virtual assistant compatibility | N/A |
| ETIM Class | EC001743 |
| Warranty | 5 ans |

Données optiques

| | |
|---------------------------------|---------------|
| Fixture luminous flux (lm) | 7000 |
| Luminaire efficacy (lm/W) | 119 |
| Température de couleur (K) | 4000 |
| Couleur de lumière | Neutral White |
| IRC (Ra) | 80 |
| Colour Variation Initial (SDCM) | SDCM3 |
| Beam Angle (°) | 84 |
| Distribution type | Symmetric |
| Glare control | < 19 |
| Photobiological Risk Group | RG0 |
| Emergency duration (h) | 3 |

Caractéristiques électriques

| | |
|--|--------------------------------|
| Consommation électrique totale (W) | 59 |
| Primary Supply/Product voltage - min (V) | 220.0 |
| Primary Supply/Product voltage - max (V) | 240.0 |
| Lamp power factor | 0.9 |
| THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x % | 20.0 |
| Electrical protection | Class I |
| Type d'appareillage | LED driver constant current |
| Dimmable | Yes |
| Dimming method | DALI-2 |
| Drive current (mA) | 1400 |
| Courant d'appel (A) | 21.7 |
| Inrush Duration (µs) | 306 |
| Energy Efficiency Class (A->G) of contained light source | C, C(more than 1 Light Source) |
| Nominal Frequency (Hz) | 50/60Hz |
| Max. products per 10A C Breaker | 14 |
| Max. products per 16A C Breaker | 23 |
| Max. products per 16A B Breaker | 23 |
| Connectable conductor cross section - Max (mm ²) | 1.5 |

Durée de vie

| | |
|------------------|--------|
| Lifespan L70 B50 | 100000 |
| Lifespan L80 B10 | 57000 |

AREUM SUSPENDED 1500 D/I 4000K DALI EM ALU

Code article 0042966

SYLVANIA

Données physiques

| | |
|-----------------------------|----------------------|
| Housing colour | RAL 9006 - Aluminium |
| IP rating | IP20 |
| IK rating | IK03 |
| Diffuser finish | Diffuse |
| Diffuser material | PS Polystyrene |
| Finition réflecteur | Not Applicable |
| Longueur (mm) | 1500 |
| Largeur (mm) | 300 |
| Nominal Product Height (mm) | 17 |
| Poids (kg) | 5.47 |

Emballage

| | |
|--------------------------------------|----------------|
| Product EAN number | 5410288429663 |
| Longueur simple de l'emballage (cm) | 155.0 |
| Largeur simple de l'emballage (cm) | 45.5 |
| Packaging single depth (cm) | 6.0 |
| DUN14 (inner) | 15410288429660 |
| Units per outer package | 4 |
| Packaging outer length / height (cm) | 156.5 |
| Packaging outer width (cm) | 47.0 |
| Packaging outer depth (cm) | 26.5 |

Sécurité

| | |
|---|------|
| Glow Wire Test (°C) | 650 |
| Condition de fonctionnement optimal (° C) | 5-35 |