


Quantum IP54 600x600 4300lm 830 SSA01D

Code article 0044608

SYLVANIA


PROTM



Quantum is a range of recessed integrated LED panels for general indoor lighting applications such as breakout areas, offices and meeting rooms. Max. drive current: 600mA; Max. power: 28W; Lifespan: 120.000Hrs L70:B50; 3000K; CRI 80; Efficacy up to: 154Lm/W; Fixture lumen: 4300lm; Glare control <19; IK03; IP54 (from the front); Class II; Equipped with SylSmart Connected bluetooth driver. Tp(a) rated diffuser that self-extinguishes within 5 sec when a flame has been removed.

Atouts techniques

Dimensions (mm)



Photométrie

Quantum IP54 600x600 4300lm 830 SSA01D

Code article 0044608

SYLVANIA

Données générales

Nom du produit	Quantum IP54 600x600 4300lm 830 SSA01D
Technologie	LED
Cap/Base	N/A
Housing	Steel
Montage	Ceiling recessed mounting
Built in presence detector	NONE
General application	Office, Education
Operating temperature range (°C)	-20°C...+40°C
Virtual assistant compatibility	N/A
ETIM Class	EC002892
Numéro virtuel FI	4279700
Warranty	5 ans

Données optiques

Fixture luminous flux (lm)	4300
Luminaire efficacy (lm/W)	154
Température de couleur (K)	3000
Couleur de lumière	Warm White
IRC (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	85
Distribution type	Symmetric
Glare control	< 19
Photobiological Risk Group	RG0

Caractéristiques électriques

Consommation électrique totale (W)	28
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.9
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	10.0
Electrical protection	Class II
Type d'appareillage	LED driver constant current
Dimmable	Yes
Dimming method	SylSmart SSA
Drive current (mA)	600
Courant d'appel (A)	20
Inrush Duration (µs)	25
Energy Efficiency Class (A->G) of contained light source	B
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	42
Max. products per 13A C Breaker	55
Max. products per 16A C Breaker	69
Max. products per 20A C Breaker	84
Max. products per 10A B Breaker	25
Max. products per 13A B Breaker	33
Max. products per 16A B Breaker	40
Max. products per 20A B Breaker	51
Connectable conductor cross section - Min (mm ²)	0.75
Connectable conductor cross section - Max (mm ²)	2.5

Quantum IP54 600x600 4300lm 830 SSA01D

Code article 0044608

SYLVANIA

Durée de vie

Lifespan L70 B50	120000
Lifespan L70 B20	120000
Lifespan L70 B10	120000
Lifespan L80 B50	105000
Lifespan L80 B20	95000
Lifespan L80 B10	85000
Lifespan L90 B50	51000
Lifespan L90 B20	47000
Lifespan L90 B10	44000

Données physiques

Housing colour	RAL 9003 - Signal white
IP rating	IP54/20
IK rating	IK03
Diffuser finish	Diffuse
Diffuser material	PS Polystyrene
Longueur (mm)	595
Largeur (mm)	595
Nominal Product Height (mm)	35
Poids (kg)	2.0

Emballage

Product EAN number	5410288446080
Longueur simple de l'emballage (cm)	62.6
Largeur simple de l'emballage (cm)	3.5
Packaging single depth (cm)	59.8
DUN14 (inner)	15410288446087
Units per outer package	4
Packaging outer length / height (cm)	63.9
Packaging outer width (cm)	16.2
Packaging outer depth (cm)	61.6

Sécurité

Glow Wire Test (°C)	650
Condition de fonctionnement optimal (° C)	-20-40