


# LIFESAFE PRO TS 1200 IP65 W EM3 NM DA

Code article 0038861

**SYLVANIA**


LiFeSafe



LiFeSafe PRO TS 1200 IP65 W EM3 NM DA. LiFeSafe PRO Twin Spot IP65 W EM3 NM DA is a wall mounted DALI addressable Twin Spot Non-Maintained 3Hr emergency duration with LiFePO4 battery. 2 x 600lm per head, 9W system power, IK08, IP65, Class II electrical construction. 6-year warranty.

## Atouts techniques

### Dimensions (mm)



### Photométrie

# LIFESAFE PRO TS 1200 IP65 W EM3 NM DA

Code article 0038861

**SYLVANIA**

## Données générales

Nom du produit	LIFESAFE PRO TS 1200 IP65 W EM3 NM DA
Technologie	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Montage	Wall surface mounted
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office
Operating temperature range (°C)	0°C...+45°C
ETIM Class	EC001957
Warranty	6 years

## Données optiques

Fixture luminous flux (lm)	1200
Luminaire efficacy (lm/W)	133
Température de couleur (K)	5000
IRC (Ra)	80
Photobiological Risk Group	RG1
Maintien du flux à la fin de la durée de vie nominale (lm)	70
Luminous flux (emergency) (lm)	1200
Flux lumineux (d'urgence) (lm)	1200
Emergency duration (h)	3

## Caractéristiques électriques

Lampe incluse	Fixture without Lightsource
Actuel (A)	0.1
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.35
THD (at 230 V, 50 Hz, full load, at 100% dimming level) $\leq$ xx.x %	84.2
Electrical protection	Class II
Control gear required	Yes
Type d'appareillage	LED driver constant current
Drive current (mA)	295
Courant d'appel (A)	30
Inrush Duration ( $\mu$ s)	3
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	80
Max. products per 13A C Breaker	104
Max. products per 16A C Breaker	129
Max. products per 20A C Breaker	161
Max. products per 10A B Breaker	121
Max. products per 13A B Breaker	104
Max. products per 16A B Breaker	129
Max. products per 20A B Breaker	161
Connectable conductor cross section - Min (mm <sup>2</sup> )	0.5
Connectable conductor cross section - Max (mm <sup>2</sup> )	1.5

## Durée de vie

Lifespan L70 B10	112000
Lifespan L90 B10	36000

# LIFESAFE PRO TS 1200 IP65 W EM3 NM DA

Code article 0038861

**SYLVANIA**

## Données physiques

Housing colour	White
IP rating	IP65
IK rating	IK08
Diffuser finish	Prismatic
Diffuser material	PC Polycarbonate
Longueur (mm)	267
Largeur (mm)	62
Nominal Product Height (mm)	260
Poids (kg)	2.0

## Emballage

Product EAN number	5410288388618
Longueur simple de l'emballage (cm)	59.0
Largeur simple de l'emballage (cm)	39.0
Packaging single depth (cm)	40.0
DUN14 (inner)	05410288388618
Units per outer package	1
Packaging outer length / height (cm)	59.0
Packaging outer width (cm)	39.0
Packaging outer depth (cm)	40.0

## Sécurité

Glow Wire Test (°C)	850
Condition de fonctionnement optimal (° C)	0 °C-45
Utilisation pour applications sèches uniquement	No