

RTS 1500MM 70W 5-WIRE WD WHITE

Code article 0042582

SYLVANIA


PROTM



RTS LED linear luminaire for industrial and commercial applications. 1500 mm length with wide optics provide homogeneous light distribution for open areas. Steel housing, White color, -25 ... +30 °C operating temperature range, 4000 K, CRI 80, 3 SDMC. 70 W power consumption, 11200 lm luminous flux, 160 lm/W efficacy, 1500 mm x 70.2 mm x 78.6 mm (L x W x H) dimensions, IP20, IK03, 220-240 V 50/60 Hz, Class I. Lifespan L70:B50 120,000 hours.

Atouts techniques

Dimensions (mm)



L	600	900	1202	1500	2403	3000	3605	4500
---	-----	-----	------	------	------	------	------	------

Photométrie

Distance [m]	Cone diameter [m]	Beam angle [°]	Beam diameter [m]	Beam diameter [ft]	Beam diameter [in]	Illuminance [lx]
0.5	1.83	90°	1.83	6.01	24.1	1672
	0.97	S(CO) 61.3° S(CO) 44.2°	0.97	3.18	12.5	3356
1.0	3.66	90°	3.66	12.02	47.3	418
	1.94	S(CO) 61.3° S(CO) 44.2°	1.94	6.36	25.0	860
1.5	5.48	90°	5.48	18.03	71.5	175
	2.92	S(CO) 61.3° S(CO) 44.2°	2.92	9.58	37.7	575
2.0	7.31	90°	7.31	24.04	94.6	104
	3.89	S(CO) 61.3° S(CO) 44.2°	3.89	12.76	50.2	210
2.5	9.13	90°	9.13	30.05	118.1	67
	4.96	S(CO) 61.3° S(CO) 44.2°	4.96	16.27	64.1	99
3.0	10.96	90°	10.96	36.06	141.6	45
	5.93	S(CO) 61.3° S(CO) 44.2°	5.93	19.41	76.4	66

RTS 1500MM 70W 5-WIRE WD WHITE

Code article 0042582

SYLVANIA

Données générales

Nom du produit	RTS 1500MM 70W 5-WIRE WD WHITE
Technologie	LED
Cap/Base	N/A
Housing	Steel
Built in presence detector	NONE
General application	Logistics & Industry
Operating temperature range (°C)	-25°C...+30°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC000986
Warranty	5 ans

Données optiques

Fixture luminous flux (lm)	11200
Luminaire efficacy (lm/W)	160
Température de couleur (K)	4000
IRC (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	90
Photobiological Risk Group	RG1

Caractéristiques électriques

Consommation électrique totale (W)	70
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.95
Electrical protection	Class I
Control gear required	No
Dimmable	No
Dimming method	N/A
Drive current (mA)	1000
Courant d'appel (A)	20
Inrush Duration (µs)	250
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 16A C Breaker	19
Max. products per 16A B Breaker	13

Durée de vie

Lifespan L70 B50	100000
Lifespan L80 B20	75000

Données physiques

Housing colour	White
IP rating	IP20
IK rating	IK03
Diffuser finish	Transparent
Diffuser material	PMMA Acrylic
Longueur (mm)	1500
Largeur (mm)	70.2
Nominal Product Height (mm)	78.6
Poids (kg)	1.7

RTS 1500MM 70W 5-WIRE WD WHITE

Code article 0042582

SYLVANIA

Emballage

Product EAN number	5410288425825
Longueur simple de l'emballage (cm)	150.0
Largeur simple de l'emballage (cm)	7.5
Packaging single depth (cm)	6.5
DUN14 (inner)	15410288425822
Units per outer package	10
Packaging outer length / height (cm)	157.0
Packaging outer width (cm)	44.0
Packaging outer depth (cm)	21.0

Sécurité

Glow Wire Test (°C)	650
Condition de fonctionnement optimal (° C)	-25-30