

Pixo Line 1500 D Asym 840 Black

Artikelnummer 0007834

SYLVANIA

PROTM



Pixo Line is a linear track system, adds flexibility to any space due the variety of product options Offers an easy installation with two separate modules Push-in/push-out mechanism with GR6d-15 connector Compatible with Zhaga Book 14 Aluminium body, plastic end caps, traslucent double asymmetric optic diffuser, light beam angle:25° black finishing colour. Light color temperature: 4000K, max. system power: 50W Max. fixture lumen output: 7600lm, efficacy: 152lm/W, Ra80 typical, LED chromacity: 3 step MacAdam ellipse (SDCM3), IR/UV free light source without heat radiation Multipower driver module with 8 power settings meet all installation needs with one single product, selection and setting on driver - between 17W (350mA), 19W (400mA), 24W (500mA), 29W (600mA), 34W (700mA), 38W (800mA), 43W (900mA), 50W (1050mA) Suitable for installation on 3-circuit tracks, please check compatibility list on the instruction sheet. Compatible with OneTrack Electrical protection: Class III. Degree of protection: IP20, suitable for indoor environment only Light modules should be combined with suitable in-track drivers Nominal product dimensions: L.1464mmx38.4mmx37mm

Technische Werte

Größe (mm)



Photometrie

| Distance [m] | Cone diameter [m] | Beam diameter [m] | Illuminance [lx] |
|--------------|-------------------|----------------------|---------------------|
| 0.5 | 0.80 1.45 | 0.07 0.09 0.10 | 4025 2863 405 |
| 1.0 | 1.59 2.90 | 0.07 0.09 0.10 | 1106 993 101 |
| 1.5 | 2.39 4.35 | 0.07 0.09 0.10 | 482 405 45 |
| 2.0 | 3.18 5.80 | 0.07 0.09 0.10 | 277 238 23 |
| 2.5 | 3.96 7.25 | 0.07 0.09 0.10 | 177 146 16 |
| 3.0 | 4.77 8.70 | 0.07 0.09 0.10 | 133 111 11 |

Distance [m] Cone diameter [m] Illuminance [lx]
 — C0 - C180 (Half beam angle: 110.0°)
 — C90 - C270 (Half beam angle: 77.0°)

Pixo Line 1500 D Asym 840 Black

Artikelnummer 0007834

SYLVANIA

Physikalische Daten

| | |
|---------------------------|-------|
| Gehäusefarbe | Black |
| IP Schutzart | IP20 |
| IK Schutzart | IK03 |
| Länge (mm) | 1464 |
| Breite (mm) | 37 |
| Nominale Produkthöhe (mm) | 38.4 |
| Gewicht (kg) | 0.9 |

Packaging

| | |
|--|----------------|
| EAN Code | 5410288078342 |
| Einzelverpackung Länge (cm) | 147.0 |
| Einzelverpackung Breite (cm) | 4.3 |
| Einzelverpackung Tiefe (cm) | 4.3 |
| DUN 14 (außen) | 15410288078349 |
| Anzahl an Einheiten je Außenverpackung | 10 |
| Außenverpackung Länge (cm) | 149.0 |
| Außenverpackung Breite (cm) | 24.0 |
| Außenverpackung Tiefe (cm) | 11.0 |

Safety data

| | |
|----------------------------------|--------|
| Glühdrahttest (°C) | 650 |
| Optimale Betriebstemperatur (°C) | -20-40 |