

# LSF PRO BH 1170 IP65 C EM3 NM/MT DA

Code article 0038826

**SYLVANIA**

LiFeSafe



LiFeSafe PRO BH 1170 IP65 C EM3 NM/MT DA is a DALI addressable LED surface or recessed LED bulkhead. Recessing mounting kit available as an accessory. Maintained or Non-Maintained, 3Hr emergency duration,. Maximum viewing distance 24m with legend kit attached. 0 to +45°C operating temperature range. 1170lm emergency output, IK10, IP65, Class II electrical construction, 6-year warranty.

## Atouts techniques

### Dimensions (mm)



### Photométrie

### Données générales

Nom du produit	LSF PRO BH 1170 IP65 C EM3 NM/MT DA
Technologie	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Montage	Ceiling surface mounting
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail
Operating temperature range (°C)	0°C...+45°C
ETIM Class	EC001957
Warranty	6 years

### Données optiques

Fixture luminous flux (lm)	1170
Luminaire efficacy (lm/W)	65
Température de couleur (K)	5000
IRC (Ra)	80
Photobiological Risk Group	RG0
Maintien du flux à la fin de la durée de vie nominale (lm)	70
Luminous flux (emergency) (lm)	1170
Flux lumineux (d'urgence) (lm)	1170
Emergency duration (h)	3

# LSF PRO BH 1170 IP65 C EM3 NM/MT DA

Code article 0038826

**SYLVANIA**

## Caractéristiques électriques

Lampe incluse	Fixture without Lightsource
Actuel (A)	0.120
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.75
THD (at 230 V, 50 Hz, full load, at 100% dimming level) $\leq$ xx.x %	21.8
Electrical protection	Class II
Control gear required	Yes
Type d'appareillage	LED driver constant current
Drive current (mA)	340
Courant d'appel (A)	50
Inrush Duration ( $\mu$ s)	220
Nominal Frequency (Hz)	50/60Hz
Max. products per 10A C Breaker	51
Max. products per 13A C Breaker	67
Max. products per 16A C Breaker	82
Max. products per 20A C Breaker	103
Max. products per 10A B Breaker	77
Max. products per 13A B Breaker	67
Max. products per 16A B Breaker	82
Max. products per 20A B Breaker	103
Connectable conductor cross section - Min (mm <sup>2</sup> )	0.5
Connectable conductor cross section - Max (mm <sup>2</sup> )	1.5

## Durée de vie

Lifespan L70 B10	112000
Lifespan L90 B10	36000

## Données physiques

Housing colour	White
IP rating	IP65
IK rating	IK10
Diffuser finish	Prismatic
Diffuser material	PC Polycarbonate
Longueur (mm)	335
Largeur (mm)	77
Nominal Product Height (mm)	135
Poids (kg)	0.46
Recessed Depth (mm)	42

## Emballage

Product EAN number	5410288388267
Longueur simple de l'emballage (cm)	52.0
Largeur simple de l'emballage (cm)	37.0
Packaging single depth (cm)	36.0
DUN14 (inner)	05410288388267
Units per outer package	1
Packaging outer length / height (cm)	52.0
Packaging outer width (cm)	37.0
Packaging outer depth (cm)	36.0

## Sécurité

Glow Wire Test (°C)	850
Condition de fonctionnement optimal (°C)	0 °C-45
Utilisation pour applications sèches uniquement	No

# LSF PRO BH 1170 IP65 C EM3 NM/MT DA

---

Code article 0038826

**SYLVANIA**