

# Concord

## Raiden IP66 3KLM 840 Symmetric Wide DALI 2824084



### Features

- Outdoor and indoor floodlight range with in house design, comes complete with 1m flying lead and adjustable bracket, aluminium housing, RAL 9022 - Pearl light grey, clear glass diffuser, IP66, IK08, Class I, 4000K, DALI dimmable, 3500lm, 26W, 135lm/W, CRI80, Symmetric Wide beam angle 60°, 100000 hrs L80B50 lifespan, 254x203x68mm (LxWxH) dimensions, 2.2kg weight.


### Product Overview

Product name	Raiden IP66 3KLM 840 Symmetric Wide DALI
Technology	LED
Cap/Base	N/A
Housing	Aluminium
General application	Logistics & Industry
ETIM Class	EC001744
Fixture luminous flux (lm)	3500
Luminaire efficacy (lm/W)	135
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	60
Photobiological Risk Group	RG1
Total power consumption (W)	26
Electrical protection	Class I
Dimmable	Yes
Housing colour	RAL 9022 - Pearl light grey
IP rating	IP66
IK rating	IK08
Product EAN number	5025768240845
Warranty	5 years


# Concord

## Raiden IP66 3KLM 840 Symmetric Wide DALI 2824084

### Photometry



### Technical drawings



### Data table

#### GENERAL DATA

**Product name**

Raiden IP66 3KLM 840 Symmetric Wide DALI

# Concord

## Raiden IP66 3KLM 840 Symmetric Wide DALI 2824084

Technology	LED
Cap/Base	N/A
Housing	Aluminium
General application	Logistics & Industry
Operating temperature range (°C)	-40°C - 50°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001744
Warranty	5 years

### OPTICAL DATA

Fixture luminous flux (lm)	3500
Luminaire efficacy (lm/W)	135
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	60
Photobiological Risk Group	RG1

### ELECTRICAL DATA

Total power consumption (W)	26
Mains voltage (V)	220-240V~
Lamp power factor	0.95
Electrical protection	Class I
Control gear required	No
Transformer required	No
Dimmable	Yes
Drive current (mA)	510
Inrush Current (A)	20
Inrush Duration (µs)	100
Glow Wire Test (°C)	850
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	56

# Concord

## Raiden IP66 3KLM 840 Symmetric Wide DALI 2824084

Max. Luminaires per 13A C Breaker	74
Max. Luminaires per 16A C Breaker	93
Max. Luminaires per 20A C Breaker	114
Max. Luminaires per 10A B Breaker	34
Max. Luminaires per 13A B Breaker	44
Max. Luminaires per 16A B Breaker	55
Max. Luminaires per 20A B Breaker	68

### LIFETIME DATA

Lifespan L70 B50	100000
Lifespan L80 B20	100000

### PHYSICAL DATA

Housing colour	RAL 9022 - Pearl light grey
IP rating	IP66
IK rating	IK08
Nominal Product Length (mm)	254
Nominal Product Width (mm)	203
Nominal Product Height (mm)	68
Nominal Product Diameter (mm)	Not applicable
Weight (kg)	2.2

### PACKAGING

Single packaging type	Carton
Product EAN number	5025768240845
Packaging single length / height (cm)	30.5
Packaging single width (cm)	20.9
Packaging single depth (cm)	12.0
DUN14 (outer)	15025768240842
Units per outer package	5
Packaging outer length / height (cm)	62.5
Packaging outer width (cm)	32.0
Packaging outer depth (cm)	32.0

# Concord

Raiden IP66 3KLM 840 Symmetric Wide DALI  
**2824084**

---

## SAFETY DATA

---

Optimal operating condition (°C)	-40-50
Special purpose lamp	No
Dry applications use only	No
Suitable for household illumination	No