

SYLPIPE L900 1300LM 830 HIGH OUTPUT

Code article 0090053

SYLVANIA

YourHome



LED T5 replacement batten, high output range: more lumens per meter with efficiency up to 125 lum/watt, seamless linking (up to 10M), ideal for direct lighting such as under cabinet or in kitchens, 120 degree beam angle, includes switch, includes 0.30m stripped cable, white polycarbonate body, includes standard and tilting brackets

Atouts techniques

Photométrie

Données générales

| | |
|---------------------------------|-------------------------------------|
| Nom du produit | SYLPIPE L900 1300LM 830 HIGH OUTPUT |
| Technologie | LED |
| Cap/Base | N/A |
| Housing | PC Polycarbonate |
| Built in presence detector | NONE |
| General application | Residential & Consumer, Retail |
| Virtual assistant compatibility | N/A |
| ETIM Class | EC000109 |
| Numéro virtuel FI | 4279465 |
| Warranty | 3 ans |

Données optiques

| | |
|----------------------------|------------|
| Fixture luminous flux (lm) | 1300 |
| Température de couleur (K) | 3000 |
| Couleur de lumière | Warm White |
| IRC (Ra) | 80 |
| Beam Angle (°) | 120 |
| Photobiological Risk Group | RG1 |

SYLPIPE L900 1300LM 830 HIGH OUTPUT

Code article 0090053

SYLVANIA

Caractéristiques électriques

| | |
|--|--------------|
| Consommation électrique totale (W) | 11 |
| Primary Supply/Product voltage - min (V) | 220 |
| Primary Supply/Product voltage - max (V) | 240 |
| Lamp power factor | 0.7 |
| Electrical protection | Class II |
| Control gear required | No |
| Type d'appareillage | Not required |
| Dimmable | No |
| Dimming method | N/A |
| Energy Efficiency Class (A->G) of contained light source | D |
| Nominal Frequency (Hz) | 50/60Hz |
| Connectable conductor cross section - Max (mm ²) | 0.75 |

Durée de vie

| | |
|------------------|-------|
| Lifespan L70 B50 | 54000 |
| Lifespan L80 B10 | 54000 |

Données physiques

| | |
|-----------------------------|-------|
| Housing colour | White |
| IP rating | IP20 |
| IK rating | IK03 |
| Longueur (mm) | 900 |
| Largeur (mm) | 24 |
| Nominal Product Height (mm) | 35 |
| Poids (kg) | 0.132 |

Emballage

| | |
|--------------------------------------|----------------|
| Product EAN number | 5410288900537 |
| Longueur simple de l'emballage (cm) | 105.2 |
| Largeur simple de l'emballage (cm) | 3.2 |
| Packaging single depth (cm) | 4.2 |
| DUN14 (inner) | 15410288900534 |
| Units per outer package | 30 |
| Packaging outer length / height (cm) | 108.1 |
| Packaging outer width (cm) | 23.5 |
| Packaging outer depth (cm) | 22.9 |

Sécurité

| | |
|---------------------|-----|
| Glow Wire Test (°C) | 650 |
|---------------------|-----|