

Pixo Line 1500 Asym R 840 White

Code article 0007836

SYLVANIA

PROTM




Pixo Line is a linear track system, adds flexibility to any space due the variety of product options Offers an easy installation with two separate modules Push-in/push-out mechanism with GR6d-15 connector Compatible with Zhaga Book 14 Aluminium body, plastic end caps, traslucent asymmetric optic diffuser, light beam angle: 25° white finishing colour. Light color temperature: 4000K, max. system power: 50W Max. fixture lumen output: 7400lm, efficacy: 148lm/W, Ra80 typical, LED chromacity: 3 step MacAdam ellipse (SDCM3), IR/UV free light source without heat radiation Multipower driver module with 8 power settings meet all installation needs with one single product, selection and setting on driver - between 17W (350mA), 19W (400mA), 24W (500mA), 29W (600mA), 34W (700mA), 38W (800mA), 43W (900mA), 50W (1050mA) Suitable for installation on 3-circuit tracks, please check compatibility list on the instruction sheet. Compatible with OneTrack Electrical protection: Class III. Degree of protection: IP20, suitable for indoor environment only Light modules should be combined with suitable in-track drivers Nominal product dimensions: L.1464mmx38.4mmx37mm

Atouts techniques

Dimensions (mm)



Photométrie



Pixo Line 1500 Asym R 840 White

Code article 0007836

SYLVANIA

Données générales

| | |
|----------------------------------|--|
| Nom du produit | Pixo Line 1500 Asym R 840 White |
| Technologie | LED |
| Cap/Base | N/A |
| Montage | Track mounting |
| General application | Hospitality, Museums & Galleries, Office, Retail |
| Operating temperature range (°C) | -20°C...+40°C |
| ETIM Class | EC000996 |
| Warranty | 5 ans |

Données optiques

| | |
|---------------------------------|----------------|
| Fixture luminous flux (lm) | 7400 |
| Luminaire efficacy (lm/W) | 148 |
| Température de couleur (K) | 4000 |
| Couleur de lumière | Neutral White |
| IRC (Ra) | 80 |
| Colour Variation Initial (SDCM) | SDCM3 |
| Beam Angle (°) | 25 |
| Photobiological Risk Group | Not applicable |

Caractéristiques électriques

| | |
|--|-----------|
| Consommation électrique totale (W) | 50 |
| Electrical protection | Class III |
| Dimmable | No |
| Dimming method | N/A |
| Energy Efficiency Class (A->G) of contained light source | D |
| Nominal Frequency (Hz) | N/A |

Durée de vie

| | |
|------------------|-------|
| Lifespan L70 B50 | 90000 |
| Lifespan L70 B20 | 90000 |
| Lifespan L70 B10 | 90000 |
| Lifespan L80 B50 | 90000 |
| Lifespan L80 B20 | 79000 |
| Lifespan L80 B10 | 76000 |
| Lifespan L90 B50 | 43000 |
| Lifespan L90 B20 | 37000 |
| Lifespan L90 B10 | 36000 |

Données physiques

| | |
|-----------------------------|-------|
| Housing colour | White |
| IP rating | IP20 |
| IK rating | IK03 |
| Longueur (mm) | 1464 |
| Largeur (mm) | 37 |
| Nominal Product Height (mm) | 38.4 |
| Poids (kg) | 0.9 |

Emballage

| | |
|--------------------------------------|----------------|
| Product EAN number | 5410288078366 |
| Longueur simple de l'emballage (cm) | 147.0 |
| Largeur simple de l'emballage (cm) | 4.3 |
| Packaging single depth (cm) | 4.3 |
| DUN14 (inner) | 15410288078363 |
| Units per outer package | 10 |
| Packaging outer length / height (cm) | 149.0 |
| Packaging outer width (cm) | 24.0 |
| Packaging outer depth (cm) | 11.0 |

Sécurité

| | |
|--|--------|
| Glow Wire Test (°C) | 650 |
| Condition de fonctionnement optimal (°C) | -20-40 |