

SYLPIPE L1500 2580LM 3CCT IP20

Code article 0090244

SYLVANIA

YourHome



LED T5 replacement batten, high output range: with efficiency up to 140 lum/watt, seamless linking (up to 10M), ideal for direct lighting such as under cabinet or in kitchens, 120 degree beam angle, includes on/off switch and colour switchable switch Warm White, Cool White or Daylight (3000K, 4000K, 6500K), includes 0.30m stripped cable, white polycarbonate body, includes standard and tilting brackets. Available in 5 lengths - 300mm, 600mm, 900mm, 1200mm and 1500mm. 30,000hrs lifetime. Additional accessories available - Connecting cables, cable with plug and additional brackets.

Atouts techniques

Photométrie

Données générales

Nom du produit	SYLPIPE L1500 2580LM 3CCT IP20
Technologie	LED
Cap/Base	N/A
Housing	PC Polycarbonate
General application	Residential & Consumer, Retail
ETIM Class	EC000109
Warranty	3 ans

Données optiques

Fixture luminous flux (lm)	2580
Luminaire efficacy (lm/W)	140
Couleur de lumière	Warm White or Neutral White or Daylight
IRC (Ra)	80
Photobiological Risk Group	RG1

Caractéristiques électriques

Consommation électrique totale (W)	19
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.5
Electrical protection	Class II
Dimmable	No
Dimming method	N/A
Courant d'appel (A)	13.1
Inrush Duration (µs)	151
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
Connectable conductor cross section - Max (mm²)	0.75

SYLPIPE L1500 2580LM 3CCT IP20

Code article 0090244



Durée de vie

Lifespan L70 B50	30000
------------------	-------

Données physiques

IP rating	IP20
IK rating	IK03
Longueur (mm)	1494
Largeur (mm)	24
Nominal Product Height (mm)	35
Poids (kg)	0.22

Emballage

Product EAN number	5410288902449
Longueur simple de l'emballage (cm)	168.0
Largeur simple de l'emballage (cm)	4.0
Packaging single depth (cm)	3.2
DUN14 (inner)	15410288902446
Units per outer package	24
Packaging outer length / height (cm)	169.5
Packaging outer width (cm)	18.5
Packaging outer depth (cm)	22.5