

OTAO LINEAR REF BLK 4PCS

Code article 0041807

SYLVANIA

PROTM



Reflector replacement modules for Otao Linear reflector versions, 3000K/4000K LED light source included, black finishing, 4 modules per pack.

Atouts techniques

Photométrie

Données générales

| | |
|----------------------------------|--|
| Nom du produit | OTAO LINEAR REF BLK 4PCS |
| Technologie | LED |
| Cap/Base | N/A |
| Housing | Aluminium |
| Montage | Ceiling recessed mounting, Ceiling surface mounting, Suspended, Wall surface mounted |
| Built in presence detector | NONE |
| General application | Office, Education |
| Operating temperature range (°C) | 5°C...+50°C |
| Virtual assistant compatibility | N/A |
| ETIM Class | EC002556 |
| Warranty | 5 ans |

Données optiques

| | |
|---------------------------------|-----------------------------|
| Couleur de lumière | Warm White or Neutral White |
| IRC (Ra) | 80 |
| Colour Variation Initial (SDCM) | SDCM3 |
| Beam Angle (°) | 80 |
| Distribution type | Symmetric |
| Glare control | < 19 |
| Photobiological Risk Group | RG1 |

Caractéristiques électriques

| | |
|--|-----------|
| Primary Supply/Product voltage - min (V) | 220.0 |
| Primary Supply/Product voltage - max (V) | 240.0 |
| Electrical protection | Class III |
| Dimmable | No |
| Dimming method | N/A |
| Energy Efficiency Class (A->G) of contained light source | D |
| Nominal Frequency (Hz) | 50/60Hz |

OTAO LINEAR REF BLK 4PCS

Code article 0041807

SYLVANIA

Durée de vie

| | |
|------------------|--------|
| Lifespan L70 B50 | 100000 |
| Lifespan L80 B50 | 100000 |

Données physiques

| | |
|---------------------|-------------------------|
| Housing colour | RAL 9003 - Signal white |
| IP rating | IP20 |
| IK rating | IK03 |
| Diffuser finish | Other |
| Diffuser material | Other |
| Finition réflecteur | Not Applicable |
| Poids (kg) | 0.25 |

Emballage

| | |
|--------------------------------------|----------------|
| Product EAN number | 5410288418070 |
| Longueur simple de l'emballage (cm) | 29.0 |
| Largeur simple de l'emballage (cm) | 5.0 |
| Packaging single depth (cm) | 13.0 |
| DUN14 (inner) | 15410288418077 |
| Units per outer package | 100 |
| Packaging outer length / height (cm) | 31.0 |
| Packaging outer width (cm) | 27.0 |
| Packaging outer depth (cm) | 29.5 |

Sécurité

| | |
|---|------|
| Glow Wire Test (°C) | 650 |
| Condition de fonctionnement optimal (° C) | 5-50 |