

Sylvania Granit IP65 0-10V 13000lm 840 WB

Code article 0039733

SYLVANIA


PROTM



Integrated LED highbay; Black aluminium housing; 13000Lm; 80 W; 163 Lm/W; 4000K; Drive current: 410mA; CRI 80; 85° beam angle; 0-10V dimmable; IP65; IK08; Lifespan L80:B20 92,000 hrs; (D x H) 298 x 168 mm; 1.5 m mains cable; 1.5 m control cable; 1.2 m chain length including hooks.

Atouts techniques

Dimensions (mm)




Photométrie

0.5	0.89	E171 E170	3426 7193
1.0	1.79	E171 E170	854 1783
1.5	2.68	E171 E170	336 702
2.0	3.58	E171 E170	214 448
2.5	4.47	E171 E170	137 288
3.0	5.36	E171 E170	92 193

Distance [m] Cone diameter [m] Illuminance [lx]

— C0 - C180 (Half beam angle: 83.6°)



Sylvania Granit IP65 0-10V 13000lm 840 WB

Code article 0039733

SYLVANIA

Données générales

Nom du produit	Sylvania Granit IP65 0-10V 13000lm 840 WB
Technologie	LED
Cap/Base	N/A
General application	Logistics & Industry
Operating temperature range (°C)	-30°C...+50°C
ETIM Class	EC001716
Numéro virtuel FI	4357099
Warranty	5 ans

Données optiques

Fixture luminous flux (lm)	13000
Luminaire efficacy (lm/W)	163
Température de couleur (K)	4000
Couleur de lumière	Neutral White
IRC (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	85
Distribution type	Symmetric
Glare control	< 25
Photobiological Risk Group	RG1

Caractéristiques électriques

Consommation électrique totale (W)	80
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.95
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	20
Electrical protection	Class I
No. Of switching cycles before premature failures	>100000
Dimmable	Yes
Dimming method	0-10V
Drive current (mA)	410
Courant d'appel (A)	80
Inrush Duration (µs)	300
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Low (6% - 20%)
Max. products per 10A C Breaker	5
Max. products per 13A C Breaker	6
Max. products per 16A C Breaker	9
Max. products per 20A C Breaker	11
Max. products per 10A B Breaker	3
Max. products per 13A B Breaker	4
Max. products per 16A B Breaker	5
Max. products per 20A B Breaker	6
Mains surge immunity (differential mode -> L-N) (kV)	6
Mains surge immunity (common mode -> L/N - GND) (kV)	6

Durée de vie

Lifespan L70 B50	120000
Lifespan L80 B20	92000
Lifespan L90 B50	51000

Sylvania Granit IP65 0-10V 13000lm 840 WB

Code article 0039733

SYLVANIA

Données physiques

Housing colour	RAL 9017 - Traffic black
IP rating	IP65
IK rating	IK08
Nominal Product Height (mm)	168
Nominal Product Diameter (mm)	298
Poids (kg)	2.243

Emballage

Product EAN number	5410288397337
Longueur simple de l'emballage (cm)	32.5
Largeur simple de l'emballage (cm)	32.5
Packaging single depth (cm)	14.5
DUN14 (inner)	05410288397337
Units per outer package	1
Packaging outer length / height (cm)	32.5
Packaging outer width (cm)	32.5
Packaging outer depth (cm)	14.5

Sécurité

Glow Wire Test (°C)	850
Condition de fonctionnement optimal (° C)	-30-50