


# OPTIX SURFACE 1200 MPO D HO 4000K DALI

Code article 2021666


## Concord



OPTIX SURFACE 1200 MPO D HO 4000K DALI is a high efficacy low glare surface or suspended LED Linear luminaire with Micro Prismatic diffuser, with direct light distribution, luminaire dimensions: 1200x200x50mm, Sylvania White body colour (RAL9016), IP20, IK07, DALI Dimmable, low LED flicker (+/-5%), Neutral White (4000K) LED Colour Temperature, 3550lm luminous flux, 31W power consumption, 114lm/W system efficacy, CRI>80, SDCM 3 (3-step MacAdam ellipse) LED Colour Consistency, UGR<20, Luminance at 65° < 3000 cd/m<sup>2</sup>, lifespan: 58,000 hours L90B10, photobiological safety risk group 1. Electrical protection Class I.

## Atouts techniques


### Dimensions (mm)



### Photométrie

Distance [m]	Cone diameter [m]	Beam diameter [m]	Beam diameter [m]	Illuminance [lx]
0.5	0.78	0.76	0.76	848
				2049
1.0	1.57	1.52	1.52	2111
				512
1.5	2.36	2.28	2.28	938
				238
2.0	3.15	3.04	3.04	523
				131
2.5	3.93	3.80	3.80	338
				85
3.0	4.72	4.55	4.55	228
				57

Distance [m] Cone diameter [m] Illuminance [lx]  
 C0 - C180 (Half beam angle: 74.4°)  
 C90 - C270 (Half beam angle: 76.4°)



# OPTIX SURFACE 1200 MPO D HO 4000K DALI

Code article 2021666

Concord

## Données générales

Nom du produit	OPTIX SURFACE 1200 MPO D HO 4000K DALI
Technologie	LED
Cap/Base	N/A
Housing	Steel
Montage	Ceiling surface mounting
Built in presence detector	NONE
General application	Education, Office
Operating temperature range (°C)	10°C...+25°C
Performance ambient temperature Tq (°C)	25
Virtual assistant compatibility	N/A
ETIM Class	EC002892
Warranty	5 ans

## Données optiques

Fixture luminous flux (lm)	3550
Luminaire efficacy (lm/W)	114
Température de couleur (K)	4000
Couleur de lumière	Neutral White
IRC (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Distribution type	Symmetric
Glare control	< 20
Photobiological Risk Group	RG1

## Caractéristiques électriques

Consommation électrique totale (W)	31
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max (V)	240
Lamp power factor	0.98
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	9
Electrical protection	Class I
Control gear required	No
Type d'appareillage	LED driver constant current
Dimmable	Yes
Dimming method	DALI
Drive current (mA)	300
Courant d'appel (A)	29
Inrush Duration (µs)	180
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	21
Max. products per 13A C Breaker	28
Max. products per 16A C Breaker	36
Max. products per 20A C Breaker	45
Max. products per 10A B Breaker	13
Max. products per 13A B Breaker	17
Max. products per 16A B Breaker	22
Max. products per 20A B Breaker	27
Connectable conductor cross section - Max (mm <sup>2</sup> )	1.5

## Durée de vie

Lifespan L70 B50	238000
Lifespan L80 B20	130000
Lifespan L90 B10	58000

# OPTIX SURFACE 1200 MPO D HO 4000K DALI

Code article 2021666

Concord

## Données physiques

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Diffuser material	PMMA Acrylic
Longueur (mm)	1200
Largeur (mm)	200
Nominal Product Height (mm)	50
Poids (kg)	4.5

## Emballage

Product EAN number	5025768216666
Longueur simple de l'emballage (cm)	122.0
Largeur simple de l'emballage (cm)	22.5
Packaging single depth (cm)	6.8
DUN14 (inner)	05025768216666
Units per outer package	1
Packaging outer length / height (cm)	122.0
Packaging outer width (cm)	22.5
Packaging outer depth (cm)	6.8

## Sécurité

Glow Wire Test (°C)	850
Condition de fonctionnement optimal (° C)	10-25