


Quantum IP54 1200x600 Multipower 6000lm 830

Code article 0044601

SYLVANIA


PROTM



Quantum is a range of recessed integrated LED panels for general indoor lighting applications such as breakout areas, offices and meeting rooms. With the help of DIP Switch multiple lumen outputs can be set up in 4 steps (32W 5200lm, 34W 5500lm, 36W 5800lm, 38W 6000lm). Max. drive current: 800mA; Lifespan: 120.000Hrs L70:B50; 3000K; CRI 80; Efficacy up to: 158Lm/W; Glare control <19; IK03; IP54 (from the front); Class II; Tp(a) rated diffuser that self-extinguishes within 5 sec when a flame has been removed.

Atouts techniques

Dimensions (mm)



Photométrie

Quantum IP54 1200x600 Multipower 6000lm 830

Code article 0044601

SYLVANIA

Données générales

Nom du produit	Quantum IP54 1200x600 Multipower 6000lm 830
Technologie	LED
Cap/Base	N/A
Housing	Steel
Montage	Ceiling recessed mounting
Built in presence detector	NONE
General application	Office, Education
Operating temperature range (°C)	-20°C...+40°C
Virtual assistant compatibility	N/A
ETIM Class	EC002892
Numéro virtuel FI	4279697
Warranty	5 ans

Données optiques

Fixture luminous flux (lm)	6000
Luminaire efficacy (lm/W)	158
Température de couleur (K)	3000
Couleur de lumière	Warm White
IRC (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	85
Distribution type	Symmetric
Glare control	< 19
Photobiological Risk Group	RG0

Caractéristiques électriques

Consommation électrique totale (W)	38
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.9
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	20.0
Electrical protection	Class II
Type d'appareillage	LED driver constant current
Dimmable	No
Dimming method	N/A
Drive current (mA)	800
Courant d'appel (A)	11.9
Inrush Duration (µs)	390
Energy Efficiency Class (A->G) of contained light source	B
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	18
Max. products per 16A C Breaker	29
Max. products per 16A B Breaker	17
Connectable conductor cross section - Min (mm ²)	0.75
Connectable conductor cross section - Max (mm ²)	2.5

Durée de vie

Lifespan L70 B50	120000
Lifespan L70 B20	120000
Lifespan L70 B10	120000
Lifespan L80 B50	105000
Lifespan L80 B20	95000
Lifespan L80 B10	85000
Lifespan L90 B50	51000
Lifespan L90 B20	47000
Lifespan L90 B10	44000

Quantum IP54 1200x600 Multipower 6000lm 830

Code article 0044601

SYLVANIA

Données physiques

Housing colour	RAL 9003 - Signal white
IP rating	IP54/20
IK rating	IK03
Diffuser finish	Diffuse
Diffuser material	PS Polystyrene
Longueur (mm)	1195
Largeur (mm)	595
Nominal Product Height (mm)	35
Poids (kg)	4.2

Emballage

Product EAN number	5410288446011
Longueur simple de l'emballage (cm)	124.3
Largeur simple de l'emballage (cm)	4.0
Packaging single depth (cm)	59.8
DUN14 (inner)	15410288446018
Units per outer package	2
Packaging outer length / height (cm)	125.6
Packaging outer width (cm)	9.6
Packaging outer depth (cm)	61.6

Sécurité

Glow Wire Test (°C)	650
Condition de fonctionnement optimal (° C)	-20-40