

ToLEDo R7S V2 118MM 850LM 840 SL

Code article 0030774


SYLVANIA



ToLEDo R7s is a retrofit replacement for traditional halogen double-ended linear R7s lamps. Omni-directional light distribution. High lumen efficacy: 122lm/W. Lumen output: 1521lm. 85% energy saving. Robust construction. Length: 118mm. Non dimmable. 15,000 hours average rated life. Ideal for domestic and commercial applications.

Atouts techniques

Dimensions (mm)



Photométrie

ToLEDo R7S V2 118MM 850LM 840 SL

Code article 0030774

SYLVANIA

Données générales

Nom du produit	ToLEDo R7S V2 118MM 850LM 840 SL
Technologie	LED
Lamp shape	Capsule
Cap/Base	R7s
Lamp finish	Clear
Built in presence detector	NONE
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Operating temperature range (°C)	-20°C...+40°C
Virtual assistant compatibility	N/A
ETIM Class	EC001959
Numéro virtuel FI	4741204
Warranty	3 ans

Données optiques

Useful luminous flux (Φuse)	850
Température de couleur (K)	4000
Couleur de lumière	Cool White
IRC (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	320
Photobiological Risk Group	RG1

Caractéristiques électriques

Power consumption (W)	7.9
Wattage (W)	7.9
Equivalent watt (W)	60
Actuel (A)	0.057
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Control gear required	No
Type d'appareillage	LED driver constant current
No. Of switching cycles before premature failures	>50000
Dimmable	No
Dimming method	N/A
Courant d'appel (A)	1.34
Inrush Duration (µs)	7180
Lamp Energy Label (class)	F
Nominal Frequency (Hz)	50/60Hz

Durée de vie

Lifespan L70 B50	15000
------------------	-------

Données physiques

Housing colour	Transparent
IP rating	IP20
Nominal Product Height (mm)	118
Nominal Product Diameter (mm)	18
Poids (kg)	0.027

ToLEDo R7S V2 118MM 850LM 840 SL

Code article 0030774

SYLVANIA

Emballage

Product EAN number	5410288307749
Longueur simple de l'emballage (cm)	4.9
Largeur simple de l'emballage (cm)	4.9
Packaging single depth (cm)	12.4
DUN14 (inner)	15410288307746
Units per outer package	6
Packaging outer length / height (cm)	15.5
Packaging outer width (cm)	10.5
Packaging outer depth (cm)	14.0

Sécurité

Condition de fonctionnement optimal (° C)	-20-40
Consignes de nettoyage en cas de bris	Not applicable
Lampe à objectif spécial	No
Utilisation pour applications sèches uniquement	Yes
Ne convient pas à l'éclairage résidentiel	Yes
Safety message	Not Suitable for totally enclosed fixtures