

# SYLPIPE L300 530LM 3CCT IP20

Code article 0090240

**SYLVANIA**

YourHome



LED T5 replacement batten, high output range: with efficiency up to 140 lum/watt, seamless linking (up to 10M), ideal for direct lighting such as under cabinet or in kitchens, 120 degree beam angle, includes on/off switch and colour switchable switch Warm White, Cool White or Daylight (3000K, 4000K, 6500K), includes 0.30m stripped cable, white polycarbonate body, includes standard and tilting brackets. Available in 5 lengths - 300mm, 600mm, 900mm, 1200mm and 1500mm. 30,000hrs lifetime. Additional accessories available - Connecting cables, cable with plug and additional brackets.

## Atouts techniques

### Photométrie

#### Données générales

Nom du produit	SYLPIPE L300 530LM 3CCT IP20
Technologie	LED
Cap/Base	N/A
Housing	PC Polycarbonate
General application	Residential & Consumer, Retail
ETIM Class	EC000109
Warranty	3 ans

#### Données optiques

Fixture luminous flux (lm)	530
Luminaire efficacy (lm/W)	133
Couleur de lumière	Warm White or Neutral White or Daylight
IRC (Ra)	80
Photobiological Risk Group	RG1

#### Caractéristiques électriques

Consommation électrique totale (W)	4
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.5
Electrical protection	Class II
Dimmable	No
Dimming method	N/A
Courant d'appel (A)	5.5
Inrush Duration (µs)	100
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
Connectable conductor cross section - Max (mm <sup>2</sup> )	0.75

# SYLPIPE L300 530LM 3CCT IP20

Code article 0090240



## Durée de vie

Lifespan L70 B50	30000
------------------	-------

## Données physiques

IP rating	IP20
IK rating	IK03
Longueur (mm)	294
Largeur (mm)	24
Nominal Product Height (mm)	35
Poids (kg)	0.065

## Emballage

Product EAN number	5410288902401
Longueur simple de l'emballage (cm)	48.0
Largeur simple de l'emballage (cm)	4.0
Packaging single depth (cm)	3.2
DUN14 (inner)	15410288902408
Units per outer package	40
Packaging outer length / height (cm)	49.5
Packaging outer width (cm)	22.5
Packaging outer depth (cm)	28.0