

# Start Batten 1500 4000/7000lm 830/840

Code article 0048979

**SYLVANIA**


**START**<sup>TM</sup>



LED batten, T8 replacement, ease of installation through 2 part push-in design of the housing, Traffic white (RAL9016) iron housing, 3900 - 7300lm (selected by DIP switches), 28 - 52W, 135-146lm/W, Integrated switch allows to choose between warm white (3000K) and neutral white (4000K) colour temperatures, CRI80, 3 step MacAdam ellipse, symmetric wide beam angle, Class I, 100000 hrs L70B50 lifespan, Non-dimmable driver, IK08, IP20, 1500 x 64 x 65mm (LxWxH) dimensions, 1.44kg weight. BESA compatibility. End cap incorporates 20mm conduit knock out.

## Atouts techniques


### Dimensions (mm)



### Photométrie

Distance [m]	Cone diameter [m]	Beam angle [°]	Beam diameter [m]	Illuminance [lx]
0.5	1.47 3.10	144.2°	55.7" 72.1"	700 650
1.0	2.93 6.19	144.2°	55.7" 72.1"	175 150
1.5	4.40 9.29	144.2°	55.7" 72.1"	77 67
2.0	5.86 12.39	144.2°	55.7" 72.1"	43 38
2.5	7.33 15.48	144.2°	55.7" 72.1"	28 25
3.0	8.80 18.58	144.2°	55.7" 72.1"	19 17

Distance [m]    Cone diameter [m]    Illuminance [lx]  
 — C0 - C180 (Half beam angle: 144.2°)  
 — C90 - C270 (Half beam angle: 111.4°)



# Start Batten 1500 4000/7000lm 830/840

Code article 0048979

**SYLVANIA**

## Données générales

Nom du produit	Start Batten 1500 4000/7000lm 830/840
Technologie	LED
Cap/Base	N/A
Housing	Steel
Built in presence detector	NONE
General application	Logistics & Industry
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
Virtual assistant compatibility	N/A
ETIM Class	EC000109
Numéro virtuel FI	4279483
Warranty	5 ans

## Données optiques

Fixture luminous flux (lm)	7300
Luminaire efficacy (lm/W)	140
Couleur de lumière	Warm White or Neutral White
IRC (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	145x110
Photobiological Risk Group	RG1

## Caractéristiques électriques

Consommation électrique totale (W)	52
Primary Supply/Product voltage - min (V)	220.0
Primary Supply/Product voltage - max (V)	240.0
Lamp power factor	0.9
THD (at 230 V, 50 Hz, full load, at 100% dimming level) ≤ xx.x %	20
Electrical protection	Class I
Control gear required	Yes
Type d'appareillage	LED driver constant current
No. Of switching cycles before premature failures	>50000
Dimmable	No
Dimming method	N/A
Drive current (mA)	350
Courant d'appel (A)	24.2
Inrush Duration (µs)	204
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. products per 10A C Breaker	12
Max. products per 13A C Breaker	15
Max. products per 16A C Breaker	19
Max. products per 20A C Breaker	25
Max. products per 10A B Breaker	10
Max. products per 13A B Breaker	11
Max. products per 16A B Breaker	13
Max. products per 20A B Breaker	15
Connectable conductor cross section - Max (mm <sup>2</sup> )	1.5

## Durée de vie

Lifespan L70 B50	100000
Lifespan L80 B50	62000

# Start Batten 1500 4000/7000lm 830/840

Code article 0048979

**SYLVANIA**

## Données physiques

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK08
Diffuser finish	Opal
Diffuser material	PC Polycarbonate
Longueur (mm)	1500
Largeur (mm)	64
Nominal Product Height (mm)	65
Poids (kg)	1.452

## Emballage

Product EAN number	5410288489797
Longueur simple de l'emballage (cm)	151.1
Largeur simple de l'emballage (cm)	6.7
Packaging single depth (cm)	6.7
DUN14 (inner)	15410288489794
Units per outer package	6
Packaging outer length / height (cm)	152.5
Packaging outer width (cm)	15.3
Packaging outer depth (cm)	22.3

## Sécurité

Glow Wire Test (°C)	650
Condition de fonctionnement optimal (° C)	-20-40